

Suction and transport hose; Medium-heavy, smooth interior, flexible at low temperatures

Applications: Special suction and transport hose, especially suitable:

- for irrigation, liquid manure conveying, sewer and sink cleaning
- for fertilizers, insecticides, purifying agents

Properties

- medium-heavy model
- smooth interior and exterior
- flexible
- good resistance to alkalis and acids

- good resistance to chemicals
- good resistance to UV and ozone
- gas and liquid tight
- conform to RoHS guideline

Temperature Range

- -25 °C approx. to +60 °C approx.

Design, material

NORPLAST® full plastic hose

1. hard plastic spiral integrated in wall spiral: rigid PVC
2. smooth interior wall: low temperature flexible soft PVC

Delivery variants


- green-transparent (standard)
- special colours: coloured spiral, full coloured
- customer-specific product marking
- customised connectors

I.D.	O.D.	Rec. operating limits		Bending Radius	Weight	Stock Lengths	Further Production Lengths	Order No.
		Overpressure	Vacuum					
mm	mm	bar	bar	mm	kg/m	m	m	
19	24	5,000	0,600	106	0,205	-	50	379-0019-0000
20	25	5,000	0,600	110	0,210	50	-	379-0020-0000
25	30	5,000	0,600	140	0,270	50	-	379-0025-0000
32	38	4,000	0,600	180	0,350	50	-	379-0032-0000
38	44	4,000	0,600	210	0,470	50	-	379-0038-0000
40	46	3,000	0,500	220	0,510	50	-	379-0040-0000
50	58	3,000	0,500	270	0,700	50	-	379-0050-0000
51	59	3,000	0,500	275	0,710	-	50	379-0051-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.


Accessories

13.4.0



NORCLAMP 211

13.18.0



NORCONNECT 270-271