



## Suction hose; Light, crush-proof, light-weight

### Applications:

- for domestic and industrial vacuum cleaners
- for cleaning swimming pools

### Properties

- light model
- highly flexible
- good resistance to alkalis and acids
- good resistance to UV and ozone
- gas and liquid tight

- crush-proof
- floatable
- light weight
- conform to RoHS guideline

### Temperature Range

- -45 °C approx. to +65 °C approx.

### Design, material

1. self-supporting profile design

2. open profile geometry wall: EVA

### Delivery variants

- grey (standard)
- as a pre-assembled hose system with NORCON-NECT connectors
- customised connectors

I.D.	O.D.	Rec. operating limits	Bending	Weight	Stock Lengths	Further Production Lengths	Order No.
mm	mm	Vacuum bar	Radius mm	kg/m	m	m	
20	26,8	0,500	52	0,130	-	30	373-0020-0000
25	32,2	0,500	66	0,150	-	30	373-0025-0000
30	38	0,500	77	0,200	-	30	373-0030-0000
32	40,4	0,500	82	0,240	<b>30</b>	-	373-0032-0000
35	43,8	0,500	88	0,260	-	30	373-0035-0000
38	47,2	0,500	93	0,310	<b>30</b>	-	373-0038-0000
40	49,4	0,500	100	0,320	-	30	373-0040-0000
45	55	0,500	111	0,370	<b>30</b>	-	373-0045-0000
50	60,4	0,500	122	0,440	<b>30</b>	-	373-0050-0000
60	72	0,500	143	0,670	-	30	373-0060-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on [www.norres.com](http://www.norres.com).

## Accessories

13.3.0



NORCLAMP 208

13.17.0



NORCONNECT 227