

High-temperature suction and blast hose; Santoprene® , super-light, highly flexible + compressible, abrasion-proof

Applications: Suction and blast hose, especially suitable:

- for powdery solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for steam extraction
- as conductor of hot and cold air
- for blowers and compressors

Properties

- very good heat resistance
- super-light model
- highly flexible + compressible
- good resistance to mineral oils and gasoline
- good resistance to alkalis and acids

- good resistance to chemicals
- small bending radius
- kink-proof
- free of softener and halogen
- gas and liquid tight
- light weight
- conform to RoHS guideline
- according to German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding the spiral, recommended for many applications with the exception of inflammable bulk materials

Temperature Range

- -40 °C approx. to +125 °C approx.
- short time to +150 °C approx.

Design, material

- PROTAPE® tape hose
1. spring steel wire integrated in wall
 2. extruded tape
wall: thermoplastic rubber (TPE)
 3. wall thickness 0.4 mm approx.

Delivery variants

- black (standard)
- special colours: full coloured
- customer-specific product marking

I.D. mm	O.D. mm	Rec. operating limits		Bending Radius mm	Weight kg/m	Stock Lengths m	Further Production Lengths m	Order No.
		Overpressure bar	Vacuum bar					
50	58	0,265	0,130	58	0,230	10	-	320-0050-0000
55	63	0,240	0,115	63	0,240	-	10	320-0055-0000
60	68	0,220	0,105	68	0,260	10	-	320-0060-0000
65	73	0,205	0,085	73	0,280	-	10	320-0065-0000
70	78	0,190	0,075	78	0,300	10	-	320-0070-0000
75	83	0,175	0,070	83	0,330	10	-	320-0075-0000
80	88	0,165	0,065	88	0,360	10	-	320-0080-0000
90	98	0,150	0,055	98	0,440	-	10	320-0090-0000
100	108	0,135	0,045	108	0,520	10	-	320-0100-0000
110	118	0,120	0,040	118	0,550	-	10	320-0110-0000
115	123	0,115	0,040	123	0,570	-	10	320-0115-0000
120	128	0,110	0,040	128	0,600	-	10	320-0120-0000
125	133	0,105	0,030	133	0,640	10	-	320-0125-0000
130	138	0,105	0,030	138	0,670	-	10	320-0130-0000
140	148	0,095	0,030	148	0,710	10	-	320-0140-0000
150	158	0,090	0,030	158	0,760	10	-	320-0150-0000
160	168	0,085	0,025	168	0,800	10	-	320-0160-0000
175	183	0,075	0,020	183	0,880	-	10	320-0175-0000
180	188	0,075	0,020	188	0,910	10	-	320-0180-0000
200	208	0,060	0,020	208	1,010	10	-	320-0200-0000
225	233	0,050	0,015	233	1,100	-	10	320-0225-0000
250	258	0,040	0,015	258	1,210	-	10	320-0250-0000
275	283	0,030	0,010	283	1,330	-	10	320-0275-0000
280	288	0,020	0,010	288	1,380	-	10	320-0280-0000
300	308	0,010	0,010	308	1,590	-	10	320-0300-0000

Santoprene® is a registered trademark of AES (Advanced Elastomer Systems); Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.



Accessories

13.1.0



NORCLAMP 212

13.6.0



NORCLAMP 217

13.7.0




NORCLAMP 213

13.14.0



NORCONNECT 223

13.18.0



NORCONNECT 270-271