



Spiral clamp with integrated earth for attaching externally corrugated spiral hoses

Properties

- grounding without exposing spiral and without damaging hose
- optional with grounding wire or ground strip
- practically leak-proof and firmly clamping with special bridge geometry
- easily and quickly fitted
- re-usable (threaded)
- rust-proof
- very robust

- conform to RoHS guideline

Design, material

1. clamp band: W2 stainless steel 1.4016 = AISI 430
2. screw: W2 galvanised steel
housing: W2 stainless steel 1.4016
3. bridge: stainless steel 1.4301/ AISI 304/ W2 (INOX)
earthing screw: stainless steel (INOX)

Suitable for Hose

AIRDUC®: 341+345, 351+355 MHF, HT-PUR 351+355, 351+355 EC, INOX 351+355 MHF, INOX 351+355 MHF-AS, 353+355, 362 EC, 362 F
TIMBERDUC®: 533, 534

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	Clamp with earthing wire Order No.
38-45	35-55	9	212-0035-2878
50-55	45-65	9	212-0045-2878
60-65	55-75	9	212-0055-2878
70-75	65-85	9	212-0065-2878
80	75-95	9	212-0075-2878
90	85-105	9	212-0085-2878
100-102	95-115	9	212-0095-2878
110-115	105-125	9	212-0105-2878
120-127	115-135	9	212-0115-2878
130	125-145	9	212-0125-2878
140	135-155	9	212-0135-2878
150-152	145-165	9	212-0145-2878
160	155-175	9	212-0155-2878
170-175	165-185	9	212-0165-2878
180	175-195	9	212-0175-2878
190	185-205	9	212-0185-2878
200	195-215	9	212-0195-2878
215	205-225	12	212-0205-2878
225	215-235	12	212-0215-2878
250	245-265	12	212-0245-2878
275	265-285	12	212-0265-2878
280	275-295	12	212-0275-2878
300	295-315	12	212-0295-2878
315-325	315-335	12	212-0315-2878
350	345-385	12	212-0345-2878
380	375-415	12	212-0375-2878
400	395-435	12	212-0395-2878
450	445-485	12	212-0445-2878
500	495-535	12	212-0495-2878

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	Clamp with earthing strip Order No.
38-45	35-55	9	212-0035-2879
50-55	45-65	9	212-0045-2879
60-65	55-75	9	212-0055-2879
70-75	65-85	9	212-0065-2879




Suitable for Hose I.D.	Clamping Range	Band Width	Clamp with earthing strip
mm	mm	mm	Order No.
80	75-95	9	212-0075-2879
90	85-105	9	212-0085-2879
100-102	95-115	9	212-0095-2879
110-115	105-125	9	212-0105-2879
120-127	115-135	9	212-0115-2879
130	125-145	9	212-0125-2879
140	135-155	9	212-0135-2879
150-152	145-165	9	212-0145-2879
160	155-175	9	212-0155-2879
170-175	165-185	9	212-0165-2879
180	175-195	9	212-0175-2879
190	185-205	9	212-0185-2879
200	195-215	9	212-0195-2879
215	205-225	12	212-0205-2879
225	215-235	12	212-0215-2879
250	245-265	12	212-0245-2879
275	265-285	12	212-0265-2879
280	275-295	12	212-0275-2879
300	295-315	12	212-0295-2879
315-325	315-355	12	212-0315-2879
350	345-385	12	212-0345-2879
380	375-415	12	212-0375-2879
400	395-435	12	212-0395-2879
450	445-485	12	212-0445-2879
500	495-535	12	212-0495-2879

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.18.0



NORCONNECT 270-271