



Hose system sub-assembled on both sides with safety clamp system; Hose system with couplings: Storz, threaded connector, etc.

Properties

- according to the German TRBS 2153 (formerly BGR 132): the metal hose spiral is fixed to the metal adapter

Temperature Range

- -40 °C approx. to +90 °C approx.
- short time to +125 °C approx.

Design, material

1. spring steel wire integrated in wall
2. clamp shells: aluminium

3. adapter: material acc. to table
4. screw and nut: chromated steel

Delivery variants

- cut lengths and special lengths
- wall: „bioplastic“ material derived from renewable raw materials without food applicability

Size mm	Thread	Total Length m	Weight kg/piece	Storz coupling, aluminium Order No.
75	G 3	3,8	11,80-13,60	230-0075-8350
75	G 3	4,8	14,00-15,80	230-0075-8351
75	G 3	5,8	16,20-18,00	230-0075-8352
100	G 4	3,8	16,60-18,70	230-0100-8350
100	G 4	4,8	19,80-21,90	230-0100-8351
100	G 4	5,8	23,00-25,10	230-0100-8352

Size mm	Thread	Total Length m	Weight kg/piece	Threaded adapter, aluminium Order No.
75	G 3	3,8	11,80-13,60	230-0075-8310
75	G 3	4,8	14,00-15,80	230-0075-8311
75	G 3	5,8	16,20-18,00	230-0075-8312
100	G 4	3,8	16,60-18,70	230-0100-8310
100	G 4	4,8	19,80-21,90	230-0100-8311
100	G 4	5,8	23,00-25,10	230-0100-8312

Size mm	Thread	Total Length m	Weight kg/piece	Threaded adapter, electro-galvanised steel Order No.
75	G 3	3,8	11,80-13,60	230-0075-8320
75	G 3	4,8	14,00-15,80	230-0075-8321
75	G 3	5,8	16,20-18,00	230-0075-8322
100	G 4	3,8	16,60-18,70	230-0100-8320
100	G 4	4,8	19,80-21,90	230-0100-8321
100	G 4	5,8	23,00-25,10	230-0100-8322

Size mm	Thread	Total Length m	Weight kg/piece	Threaded adapter stainless steel 1.4301 (stamped) = AISI 304 Order No.
75	G 3	3,8	11,80-13,60	230-0075-8330
75	G 3	4,8	14,00-15,80	230-0075-8331
75	G 3	5,8	16,20-18,00	230-0075-8332
100	G 4	3,8	16,60-18,70	230-0100-8330
100	G 4	4,8	19,80 - 21,90	230-0100-8331
100	G 4	5,8	23,00 - 25,10	230-0100-8332



Size mm	Thread	Total Length m	Weight kg/piece	Threaded adapter, stainless steel 1.4404 Order No.
75	G 3	3,8	11,80-13,60	230-0075-8340
100	G 3	4,8	14,00-15,80	230-0075-8341
75	G 3	5,8	16,20-18,00	230-0075-8342
100	G 4	3,8	16,60-18,70	230-0100-8340
100	G 4	4,8	19,80-21,90	230-0100-8341
100	G 4	5,8	23,00-25,10	230-0100-8342

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.