

Abrasion-proof suction and blast hose; Super-light and reinforced, highly flexible + compressible 3:1, antistatic

Applications: Abrasion-proof suction and blast hose, especially suitable:

- for abrasive solids such as dust, powder, fibres and chips
- for gaseous media such as oil vapors and welding smoke
- for de-dusting and suction plants

Properties

- super-light and reinforced model
- highly flexible + compressible 3:1
- abrasion-proof (abrasion resistance about 2.5 to 5 times better than most rubber materials and about 3 to 4 times better than most soft PVC 's)
- optimized flow properties
- high tensile strength and tear resistant
- food grade wall, complies with: FDA 21 CFR 177.2600 and 178.2010, EU Directive 2002/72 /EC, incl. amending Directives 975/2009 and Regulation No. 10/2011

- approved by an independent testing laboratory for the complete hose acc. to EU Directive 2002 /72/EC, incl. amending Directives 2008/39/EC and 975/2009
- microbe and hydrolysis resistant
- good resistance to mineral oils and gasoline
- good resistance to chemicals
- good resistance to UV and ozone
- very good low temperature flexibility (better than comparable ester-polyurethanes)
- small bending radius
- kink-proof
- free of softener and halogen
- gas and liquid tight
- conform to RoHS guideline
- according to German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding, recommended for many applications with the exception of inflammable bulk materials

Temperature Range

- -40 °C approx. to +90 °C approx.
- short time to +125 °C approx.

Design, material

- PROTAPE® tape hose
1. spring steel wire integrated in wall
 2. extruded tape
wall: special premium ether-polyurethane (Pre-PUR®)
 3. wall thickness 0.6 mm approx.

Delivery variants

- cut lengths and special lengths
- transparent (standard)
- special colours: partially coloured, completely coloured
- customer-specific product marking
- wall: „bioplastic“ material derived from renewable raw materials without food applicability
- customised connectors

I.D. mm	O.D. mm	Rec. operating limits		Bending Radius mm	Weight kg/m	Stock Lengths m	Further Production Lengths m	Order No.
		Overpressure bar	Vacuum bar					
25	32	1,600	0,360	32	0,170	10	15	330-0025-0000
30	37	1,345	0,340	37	0,200	10	15	330-0030-0000
32	39	1,260	0,340	39	0,210	10 15	-	330-0032-0000
38	45	1,060	0,320	45	0,250	10 15	-	330-0038-0000
40	47	1,015	0,300	47	0,280	10 15	-	330-0040-0000
45	52	0,900	0,285	52	0,310	-	10 15	330-0045-0000
50	58	0,815	0,260	58	0,360	10 15	-	330-0050-0000
51	59	0,800	0,260	59	0,370	10	15	330-0051-0000
60	68	0,680	0,210	68	0,430	10 15	-	330-0060-0000
63	71	0,645	0,195	71	0,450	10	15	330-0063-0000
65	73	0,630	0,180	73	0,470	10	15	330-0065-0000
70	78	0,585	0,150	78	0,500	10 15	-	330-0070-0000
75	83	0,545	0,140	83	0,530	10	15	330-0075-0000
76	84	0,540	0,140	84	0,540	-	10 15	330-0076-0000
80	88	0,510	0,130	88	0,570	10 15	-	330-0080-0000
90	98	0,455	0,115	98	0,630	10	15	330-0090-0000
100	108	0,410	0,090	108	0,660	10	15	330-0100-0000
102	110	0,400	0,090	110	0,680	10	15	330-0102-0000
110	118	0,375	0,080	118	0,730	10	15	330-0110-0000
115	123	0,355	0,080	123	0,760	10	15	330-0115-0000
120	128	0,340	0,075	128	0,790	10	15	330-0120-0000
125	133	0,330	0,060	133	0,820	10 15	-	330-0125-0000
127	135	0,325	0,060	135	0,830	10	15	330-0127-0000
130	138	0,315	0,060	138	0,850	10	15	330-0130-0000
140	148	0,295	0,060	148	0,920	10	15	330-0140-0000
150	158	0,275	0,055	158	0,980	10 15	-	330-0150-0000



I.D.	O.D.	Rec. operating limits		Bending Radius	Weight	Stock Lengths	Further Production Lengths	Order No.
		Overpressure	Vacuum					
mm	mm	bar	bar	mm	kg/m	m	m	
152	160	0,270	0,055	160	0,990	10	15	330-0152-0000
160	168	0,255	0,050	168	1,040	10	15	330-0160-0000
170	178	0,240	0,045	178	1,110	10	15	330-0170-0000
175	183	0,235	0,040	183	1,140	10	15	330-0175-0000
178	186	0,230	0,040	186	1,160	-	10 15	330-0178-0000
180	188	0,230	0,040	188	1,170	10	15	330-0180-0000
200	208	0,205	0,040	208	1,540	10	15	330-0200-0000
203	211	0,205	0,040	211	1,570	10	15	330-0203-0000
225	233	0,180	0,030	233	1,750	10	15	330-0225-0000
228	236	0,180	0,028	236	1,770	-	10 15	330-0228-0000
250	258	0,165	0,015	258	1,900	10	15	330-0250-0000
254	262	0,165	0,015	262	1,940	-	10 15	330-0254-0000
275	283	0,150	0,015	283	2,110	-	10	330-0275-0000
280	288	0,145	0,015	288	2,150	-	10	330-0280-0000
300	309	0,135	0,015	309	2,530	10	-	330-0300-0000
305	314	0,135	0,015	314	2,570	-	10	330-0305-0000
315	324	0,130	0,010	324	2,650	-	10	330-0315-0000
325	334	0,125	0,010	334	2,740	-	10	330-0325-0000
350	359	0,115	0,010	359	2,950	10	-	330-0350-0000
400	409	0,105	0,010	409	3,360	10	-	330-0400-0000
450	459	0,090	0,006	459	3,770	-	10	330-0450-0000
500	510	0,080	0,005	510	5,160	-	10	330-0500-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.1.0



NORCLAMP 212

13.6.0




NORCLAMP 217

13.7.0




NORCLAMP 213

13.14.0



NORCONNECT 223

13.18.0



NORCONNECT 270-271