



Exhaust gas hose; Crush-proof, light (exhaust gas temperatures up to +200 °C*)

Applications: Special exhaust gas hose, especially suitable:

- for suction of engine exhaust gas
- for hose reel
- for slotted floor channels
- for above and below floor suction extraction

- fabric reinforced
- good resistance to chemicals
- small bending radius
- gas and liquid tight
- light weight
- conform to RoHS guideline

Design, material

- PROTAPE® tape hose
1. special plastic-profile supporting spiral
 2. fabric-reinforced tape wall: EPDM/ PP coated fabric
 3. wall thickness 0.4 mm approx.

Properties

- vibration resistant
- crush-proof
- highly flexible + compressible
- flow-optimizing exterior folds

Temperature Range

- exhaust gas temperatures to +200 °C *
- * when correctly applied with exhaust gas funnels and sufficient fresh air supply (50% approx.).

Delivery variants

- black (standard)
- special colours: coloured spiral
- customer-specific product marking

I.D.	O.D.	Rec. operating limits	Bending	Weight	Stock Lengths	Further Production Lengths	Order No.
mm	mm	Vacuum bar	Radius mm	kg/m	m	m	
50	67	0,400	80	0,410	-	2,5 5 7,5 10 12,5 15	326-0050-0000
51	68	0,400	82	0,420	15	2,5 5 7,5 10 12,5	326-0051-0000
63	80	0,280	101	0,510	15	2,5 5 7,5 10 12,5	326-0063-0000
76	93	0,170	111	0,610	15	2,5 5 7,5 10 12,5	326-0076-0000
80	97	0,130	116	0,640	-	2,5 5 7,5 10 12,5 15	326-0080-0000
100	117	0,050	120	0,780	-	2,5 5 7,5 10 12,5 15	326-0100-0000
102	119	0,050	122	0,800	15	2,5 5 7,5 10 12,5	326-0102-0000
125	142	0,035	144	0,970	-	2,5 5 7,5 10 12,5 15	326-0125-0000
127	144	0,035	152	0,980	15	2,5 5 7,5 10 12,5	326-0127-0000
150	167	0,030	180	1,150	-	2,5 5 7,5 10 12,5 15	326-0150-0000
152	169	0,030	182	1,160	15	2,5 5 7,5 10 12,5	326-0152-0000
200	217	0,010	240	1,500	-	2,5 5 7,5 10 12,5 15	326-0200-0000
203	220	0,010	244	1,520	15	2,5 5 7,5 10 12,5	326-0203-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

