



Aseptic coupling system acc. to DIN 11864-3

Properties

- food grade wall, complies with: EU Directive 2002/72/EC, incl. the latest Amending Directive 975/2009/EC
- conform to RoHS guideline
- according to the German TRBS 2153 (formerly BGR 132): the metal hose spiral is fixed to the metal adapter

Temperature Range

- -40 °C approx. to +90 °C approx.

Design, material

wall: special premium ether-polyurethane (Pre-PUR®)
 fitting: stainless steel 1.4404 (stamped) = AISI 316L

Delivery variants

- transparent (standard)
- special colours: full coloured
- as a pre-assembled hose system with a suitable hose

- customised connectors
- other accessories on www.norres.com

Suitable for Hose

AIRDUC®: 351+355+356 MHF, INOX 351+355 MHF-AS, INOX 351+355 MHF

Size	Outer-Ø Flange	I.D. d1	I.D. Hose	Weight	Suitable for Hose	Pre-fitted
mm	mm	mm	mm	kg/piece	I.D. mm	Clamp DIN 11846-3 Order No.
25	50,5	26	25	0,21	351-355 ø 25	249-0025-8970
32	50,5	32	32	0,25	351-356 ø 32	249-0032-8970
40	64	38	40	0,30	351-356 ø 40	249-0040-8970
50	77,5	50	50	0,50	351-356 ø 50	249-0050-8970
65	91	66	65	0,62	351-356 ø 65	249-0065-8970
80	106	81	80	0,85	351-356 ø 80	249-0080-8970
100	130	100	100	1,02	351-356 ø 100	249-0100-8970

Other diameters available on request.; All stated data are approx. figures based on a temperature of 20 °C. Engineering modifications subject to change. Please refer to the technical appendix.