

**TRI-Clamp coupling to fit adapter acc. to DIN 32676****Properties**

- vibration resistant
- smooth interior
- high tensile strength and tear resistant
- food grade wall, complies with: EU Directive 2002/72/EC, incl. the latest Amending Directive 975/2009/EC
- odourless and tasteless
- microbe and hydrolysis resistant
- good resistance to mineral oils and gasoline
- good resistance to chemicals
- good resistance to UV and ozone
- free of softener and halogen
- gas and liquid tight as pre-fitted version

- easily and quickly fitted
- rust-proof
- conform to RoHS guideline

Temperature Range

- -40 °C approx. to +90 °C approx.

Design, material

wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- black (standard)
- special colours: full coloured

- as a pre-assembled hose system with a suitable hose
- gas and liquid tight as pre-fitted version
- other accessories on www.norres.com
- customised connectors

Suitable for Hose

AIRDUC®: 341+345, 351+355+356 MHF, 351+355+356 EC, INOX 351+355+356 MHF-AS, INOX 351+355+356 MHF, 353+355+356
TIMBERDUC®: 533, 534

Size	Outer-Ø Flange	Pipe i.d.	Total Length	Weight	Suitable for Hose I.D.	Threaded (pre-fitted on request) Order No.
mm	mm	mm	mm	kg/piece	mm	
32	50,5	32	60	0,06	351-355,533-534,341-345 ø 32	245-0032-8500
32	50,5	32	60	0,06	341-345 ø 32	245-0032-8500
32	50,5	32	60	0,06	356 ø 32	245-0032-8501
38	50,5	38	65	0,07	351-355,533-534,341-345 ø 38	245-0038-8500
38	50,5	38	65	0,07	341-345 ø 38	245-0038-8500
38	50,5	38	65	0,07	356 ø 38	245-0038-8501
50	64	50	67	0,12	351-355,533-534,341-345 ø 50	245-0050-8500
50	64	50	67	0,12	341-345 ø 50	245-0050-8500
50	64	50	67	0,12	356 ø 50	245-0050-8501
65	91	66	67	0,18	351-355,533-534,341-345 ø 65	245-0065-8500
65	91	66	67	0,18	341-345 ø 65	245-0065-8500
65	91	66	67	0,18	356 ø 65	245-0065-8501
80	106	81	72	0,20	351-355,533-534,341-345 ø 80	245-0080-8500
80	106	81	72	0,20	341-345 ø 80	245-0080-8500
80	106	81	72	0,20	356 ø 80	245-0080-8501
100	119	100	77	0,33	351-355,533-534,341-345 ø 100	245-0100-8500
100	119	100	77	0,33	341-345 ø 100	245-0100-8500
100	119	100	77	0,33	356 ø 100	245-0100-8501
125	155	125	91	0,48	351-355,533-534,341-345 ø 125	245-0125-8500
125	155	125	91	0,48	341-345 ø 125	245-0125-8500
125	155	125	91	0,48	356 ø 125	245-0125-8501
150	183	150	102	0,67	351-355,533-534,341-345 ø 150	245-0150-8500
150	183	150	102	0,67	341-345 ø 150	245-0150-8500
150	183	150	102	0,67	356 ø 150	245-0150-8501
200	233,5	200	112,5	0,96	351-355,533-534,341-345 ø 200	245-0200-8500
200	233,5	200	112,5	0,96	341-345 ø 200	245-0200-8500
200	233,5	200	112,5	0,96	356 ø 200	245-0200-8501

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.