



Soft sleeve for EVA hoses

Properties

- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- easily and quickly fitted
- re-usable (threaded)
- conform to RoHS guideline

Temperature Range

- -20 °C approx. to +70 °C approx.
- short time to +80 °C approx.

Design, material

wall: high grade soft PVC
 wall version electrically conductive <math> < 10^4 \Omega </math>: electrically conductive premium ester-polyurethane (Pre-PUR®)

Delivery variants

- grey (standard)
- black (standard)
- as a pre-assembled hose system with a suitable hose

Suitable for Hose

EVA: 373, 373 AS, 373 EC

Recommended Adapter Ø	Recommended Adapter Length	Threading depth Hose	Total Length	Weight	Suitable for Hose	Dimensions in Stock
						I.D.
mm	mm	mm	mm	kg/piece	mm	Colour grey Order No.
32	44	40	85	0,06	32	227-0032-0000
38	44	40	85	0,07	38	227-0038-0000
45	44	40	90	0,08	45	227-0045-0000
50	49	41	90	0,09	50	227-0050-0000

Recommended Adapter Ø	Recommended Adapter Length	Threading depth Hose	Total Length	Weight	Suitable for Hose	Dimensions in Stock
						I.D.
mm	mm	mm	mm	kg/piece	mm	Colour Black Order No.
32	44	40	85	0,06	32	227-0032-0001
38	44	40	85	0,07	38	227-0038-0001
45	44	40	90	0,08	45	227-0045-0001
50	49	41	90	0,09	50	227-0050-0001

Recommended Adapter Ø	Recommended Adapter Length	Threading depth Hose	Total Length	Weight	Suitable for Hose	Dimensions in Stock
						I.D.
mm	mm	mm	mm	kg/piece	mm	Electrically conductive <math> < 10^4 \Omega </math> Colour Black
32	44	40	85	0,06	32	227-0032-1003
38	44	40	85	0,07	38	227-0038-1003
45	44	40	90	0,08	45	227-0045-1003
50	49	41	90	0,09	50	227-0050-1003

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.