



Shrink hose for connecting one hose to another or to an adapter

Properties

- adapts itself to any surface
- easily and quickly fitted
- perfectly bonded and sealed connection with warm-melt adhesive
- conform to RoHS guideline

Temperature Range

- -40 °C approx. to +125 °C approx.

Design, material

polyolefine

Delivery variants

- black (standard)
- as a pre-assembled hose system with a suitable hose
- hot melt adhesive available on request
- other accessories on www.norres.com

Suitable for Hose

PROTAPE®: 301, 310, 320, 322 EC, 330+331 MHF, INOX 330 MHF-AS, INOX 330 MHF, 370, 371
 NORPLAST®: 383, 385, 388 SUPERELASTIC
 AIRDUC®: 341+345, 350+351+355 MHF, INOX 351+355 MHF, INOX 351+355 MHF-AS, PUR 351+355 EC, 353+355, 362 EC, 362 F, 363
 SuperFlex: PVC 372
 TIMBERDUC®: 531+533+534 SE
 NEO: 1+2

Suitable for Hose	Shrinking Range	Muff Length approx.	PU	Dimensions in Stock
I.D. mm	mm	mm	pieces	Order No.
15-22	15-30	70	1	223-0038-0000
15-22	15-30	1000	1	223-0038-9001
20-40	22-50	80	1	223-0050-0000
20-40	22-50	1000	1	223-0050-9001
30-50	25-63	80	1	223-0063-0000
30-50	25-63	1000	1	223-0063-9001
40-60	30-75	90	1	223-0075-0000
40-60	30-75	1000	1	223-0075-9001
50-70	35-85	100	1	223-0085-0000
50-70	35-85	1000	1	223-0085-9001
60-80	40-95	110	1	223-0095-0000
60-80	40-95	1000	1	223-0095-9001
80-100	45-115	120	1	223-0115-0000
80-100	45-115	1000	1	223-0115-9001
100-130	50-140	150	1	223-0140-0000
100-130	50-140	1000	1	223-0140-9001
130-150	60-160	170	1	223-0160-0000
130-150	60-160	1000	1	223-0160-9001
150-170	70-180	190	1	223-0180-0000
150-170	70-180	1000	1	223-0180-9001

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.


Accessories

13.3.0



NORCLAMP 208

13.18.0



NORCONNECT 270-271