



Clamp for attachment of light-duty hoses with smooth exterior

Properties

- easily and quickly fitted
- re-usable (threaded)
- rust-proof
- conform to RoHS guideline

Design, material

1. clamp band: W1 galvanised steel, W2 stainless steel 1.4016 = AISI 430, W4 stainless steel 1.4301 = AISI 304

2. screw: W1 galvanised steel, W2 stainless steel, W4 stainless steel 1.4301 = AISI 304
housing: W1 galvanised steel, W2 stainless steel 1.4016, W4 stainless steel 1.4301 = AISI 304

Suitable for Hose

NEO 1+2, SIL 1+2
 PROTAPÉ®: 335 MHF FLAT, CU 335 MHF FLAT, 370
 SuperFlex: PVC 372
 EVA: 373, 373 AS, 373 EC
 NORPLAST®: 385
 NORPLAST®: 383, 388 SUPERELASTIC
 PROTAPÉ®: 371
 NORFLEX®: 401+441 MHF
 NORFLEX®: 400+440
 NORFLEX®: 408+448

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	PU pcs.	Dimensions in Stock Order No. W1
8-9	8-12	9	1	208-0008-0000
10-11	10-16	9	1	208-0010-0000
12-15	12-20	9	1	208-0012-0000
16-19	16-25	9	1	208-0016-0000
20-24	20-32	9	1	208-0020-0000
25-31	25-40	9	1	208-0025-0000
32-39	32-50	9	1	208-0032-0000
40-49	40-60	9	1	208-0040-0000
50-59	50-70	9	1	208-0050-0000
60-69	60-80	9	1	208-0060-0000
80-89	80-100	9	1	208-0080-0000
90-99	90-110	9	1	208-0090-0000
100-109	100-120	9	1	208-0100-0000
110-119	110-130	9	1	208-0110-0000
120-129	120-140	9	1	208-0120-0000
130-139	130-150	9	1	208-0130-0000
140-149	140-160	9	1	208-0140-0000
150-159	150-170	9	1	208-0150-0000
160-169	160-180	9	1	208-0160-0000
170-179	170-190	9	1	208-0170-0000
180-189	180-200	9	1	208-0180-0000
190-199	190-210	9	1	208-0190-0000
200-210	200-220	9	1	208-0200-0000
220-229	220-240	12	1	208-0220-0000
250	250-270	12	1	208-0250-0000
280	280-300	12	1	208-0280-0000
300	300-320	12	1	208-0300-0000
320-325	320-340	12	1	208-0320-0000
350	350-370	12	1	208-0350-0000
400	400-420	12	1	208-0400-0000
450	450-470	12	1	208-0450-0000
500	500-520	12	1	208-0500-0000

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	PU pcs.	Dimensions in Stock Order No. W1
8-9	8-12	9	100	208-0008-9100
10-11	10-16	9	100	208-0010-9100
12-15	12-20	9	100	208-0012-9100
16-19	16-25	9	100	208-0016-9100
20-24	20-32	9	100	208-0020-9100
25-31	25-40	9	100	208-0025-9100
32-39	32-50	9	50	208-0032-9050
40-49	40-60	9	50	208-0040-9050
50-59	50-70	9	50	208-0050-9050
60-69	60-80	9	50	208-0060-9050
70-79	70-90	9	25	208-0070-9025
80-89	80-100	9	25	208-0080-9025
90-99	90-110	9	25	208-0090-9025
110-119	110-130	9	10	208-0110-9010
120-129	120-140	9	10	208-0120-9010
130-139	130-150	9	10	208-0130-9010
140-149	140-160	9	10	208-0140-9010
150-159	150-170	9	10	208-0150-9010
160-169	160-180	9	10	208-0160-9010
170-179	170-190	9	10	208-0170-9010
180-189	180-200	9	10	208-0180-9010
190-199	190-210	9	10	208-0190-9010
200-210	200-220	9	10	208-0200-9010

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	PU pcs.	Order No. W2
8-9	8-12	9	1	208-0008-9200
10-11	10-16	9	1	208-0010-9200
12-15	12-20	9	1	208-0012-9200
16-19	16-25	9	1	208-0016-9200
20-24	20-32	9	1	208-0020-9200
25-31	25-40	9	1	208-0025-9200
32-39	32-50	9	1	208-0032-9200
40-49	40-60	9	1	208-0040-9200
50-59	50-70	9	1	208-0050-9200
60-69	60-80	9	1	208-0060-9200
70-79	70-90	9	1	208-0070-9200
80-89	80-100	9	1	208-0080-9200
90-99	90-110	9	1	208-0090-9200
100-109	100-120	9	1	208-0100-9200
110-119	110-130	9	1	208-0110-9200
120-129	120-140	9	1	208-0120-9200
130-139	130-150	9	1	208-0130-9200
140-149	140-160	9	1	208-0140-9200
150-159	150-170	9	1	208-0150-9200
160-169	160-180	9	1	208-0160-9200
170-179	170-190	9	1	208-0170-9200
180-189	180-200	9	1	208-0180-9200
190-199	190-210	9	1	208-0190-9200
200-210	200-220	9	1	208-0200-9200
220-229	220-240	12	1	208-0220-9200
250	250-270	12	1	208-0250-9200
280	280-300	12	1	208-0280-9200
300	300-320	12	1	208-0300-9200

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	PU pcs.	Order No. W2
320-325	320-340	12	1	208-0320-9200
350	350-370	12	1	208-0350-9200
400	400-420	12	1	208-0400-9200
450	450-470	12	1	208-0450-9200
500	500-520	12	1	208-0500-9200
8-9	8-12	9	100	208-0008-9220
10-11	10-16	9	100	208-0010-9220
12-15	12-20	9	100	208-0012-9220
16-19	16-25	9	100	208-0016-9220
20-24	20-32	9	100	208-0020-9220
25-31	25-40	9	100	208-0025-9220
32-39	32-50	9	50	208-0032-9215
40-49	40-60	9	50	208-0040-9215
50-59	50-70	9	50	208-0050-9215
60-69	60-80	9	50	208-0060-9215
70-79	70-90	9	25	208-0070-9210
80-89	80-100	9	25	208-0080-9210
90-99	90-110	9	25	208-0090-9210
100-109	100-120	9	25	208-0100-9210
110-119	110-130	9	10	208-0110-9205
120-129	120-140	9	10	208-0120-9205
130-139	130-150	9	10	208-0130-9205
140-149	140-160	9	10	208-0140-9205
150-159	150-170	9	10	208-0150-9205
160-169	160-180	9	10	208-0160-9205
170-179	170-190	9	10	208-0170-9205
180-189	180-200	9	10	208-0180-9205
190-199	190-210	9	10	208-0190-9205
200-210	200-220	9	10	208-0200-9205

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	PU pcs.	Order No. W4
8-9	8-12	9	1	208-0008-9230
10-11	10-16	9	1	208-0010-9230
12-15	12-20	9	1	208-0012-9230
16-19	16-25	9	1	208-0016-9230
20-24	20-32	9	1	208-0020-9230
25-31	25-40	9	1	208-0025-9230
32-39	32-50	9	1	208-0032-9230
40-49	40-60	9	1	208-0040-9230
50-59	50-70	9	1	208-0050-9230
60-69	60-80	9	1	208-0060-9230
70-79	70-90	9	1	208-0070-9230
80-89	80-100	9	1	208-0080-9230
90-99	90-110	9	1	208-0090-9230
100-109	100-120	9	1	208-0100-9230
110-119	110-130	9	1	208-0110-9230
120-129	120-140	9	1	208-0120-9230
130-139	130-150	9	1	208-0130-9230
140-149	140-160	9	1	208-0140-9230
150-159	150-170	9	1	208-0150-9230
160-169	160-180	9	1	208-0160-9230
170-179	170-190	9	1	208-0170-9230
180-189	180-200	9	1	208-0180-9230

Suitable for Hose I.D. mm	Clamping Range mm	Band Width mm	PU pcs.	Order No. W4
190-199	190-210	9	1	208-0190-9230
200-210	200-220	9	1	208-0200-9230
220-229	220-240	12	1	208-0220-9230
250	250-270	12	1	208-0250-9230
280	280-300	12	1	208-0280-9230
300	300-320	12	1	208-0300-9230
320-325	320-340	12	1	208-0320-9230
350	350-370	12	1	208-0350-9230
400	400-420	12	1	208-0400-9230
450	450-470	12	1	208-0450-9230
500	500-520	12	1	208-0500-9230
8-9	8-12	9	100	208-0008-9250
10-11	10-16	9	100	208-0010-9250
12-15	12-20	9	100	208-0012-9250
16-19	16-25	9	100	208-0016-9250
20-24	20-32	9	100	208-0020-9250
25-31	25-40	9	100	208-0025-9250
32-39	32-50	9	50	208-0032-9245
40-49	40-60	9	50	208-0040-9245
50-59	50-70	9	50	208-0050-9245
60-69	60-80	9	50	208-0060-9245
70-79	70-90	9	25	208-0070-9240
80-89	80-100	9	25	208-0080-9240
90-99	90-110	9	25	208-0090-9240
100-109	100-120	9	25	208-0100-9240
110-119	110-130	9	10	208-0110-9235
120-129	120-140	9	10	208-0120-9235
130-139	130-150	9	10	208-0130-9235
140-149	140-160	9	10	208-0140-9235
150-159	150-170	9	10	208-0150-9235
160-169	160-180	9	10	208-0160-9235
170-179	170-190	9	10	208-0170-9235
180-189	180-200	9	10	208-0180-9235
190-199	190-210	9	10	208-0190-9235
200-210	200-220	9	10	208-0200-9235


Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories



13.14.0

NORCONNECT 223



13.18.0

NORCONNECT 270-271