

Metal hose connector / reducer

Properties

- easily and quickly fitted
- re-usable (threaded)
- rust protected
- conform to RoHS guideline

Temperature Range

- +400 °C approx.

Design, material

galvanised sheet metal

Delivery variants

- Stainless Steel (INOX)

Suitable for Hose

PROTAPE®: 301, 310, 320, 322 EC, 326
 MEMORY, 327 MEMORY, 330 MHF, INOX 330

MHF-AS, INOX 330 MHF, 335 MHF, CU 335 MHF
 FLAT, 370, 371
 AIRDUC®: 341+345, 350-355 MHF, HT-PUR
 351+355, INOX 351+355 MHF-AS, 351+355 EC,
 INOX 351+355 MHF, 353+355, 355 CSH, 355
 REINFORCED, 355 ORANGE, 362 EC, 362 F, 363
 NORPLAST®: 380 GREEN, 379 GREEN SUPER-
 ELASTIC, 383, 385, CU 386, 384, CU 384, 388
 SUPERELASTIC
 CP: 450, 450+461 PROTECT, 455 MHF, 457, 459
 EC, 460, 461, INOX 471+472+475 EC+475 F,
 HiTex 480-487
 SuperFlex: PVC 372
 NEO: 1+2
 SIL: 1+2

Suitable for Hose I.D. d1	Suitable for Hose I.D. d2	Adapter length I1	Adapter length I2	Total Length I3	Wall Thickness	Weight	Dimensions in Stock
mm	mm	mm	mm	mm	mm	kg/piece	Order No.
50	50	40	40	90	0,6	0,2	270-0050-0000
60	60	40	40	90	0,6	0,2	270-0060-0000
70	70	40	40	90	0,6	0,2	270-0070-0000
75	75	40	40	90	0,6	0,2	270-0075-0000
80	80	40	40	90	0,6	0,2	270-0080-0000
90	90	40	40	90	0,6	0,2	270-0090-0000
100	100	40	40	90	0,6	0,2	270-0100-0000
110	110	40	40	90	0,6	0,3	270-0110-0000
120	120	40	40	90	0,6	0,3	270-0120-0000
125	125	40	40	90	0,6	0,3	270-0125-0000
130	130	40	40	90	0,6	0,3	270-0130-0000
140	140	40	40	90	0,6	0,4	270-0140-0000
150	150	40	40	90	0,6	0,5	270-0150-0000
160	160	40	40	90	0,6	0,5	270-0160-0000
170	170	40	40	90	0,6	0,5	270-0170-0000
175	175	40	40	90	0,6	0,6	270-0175-0000
180	180	40	40	90	0,6	0,6	270-0180-0000
200	200	40	40	90	0,6	0,6	270-0200-0000
215	215	40	40	90	0,6	0,7	270-0215-0000
225	225	40	40	90	0,6	0,7	270-0225-0000
250	250	60	60	130	0,6	0,8	270-0250-0000
275	275	60	60	130	0,6	0,9	270-0275-0000
300	300	60	60	130	0,7	1,00	270-0300-0000
315	315	60	60	130	0,7	1,1	270-0315-0000
325	325	60	60	130	0,7	1,2	270-0325-0000
350	350	60	60	130	0,7	1,3	270-0350-0000
375	375	80	80	170	0,7	1,5	270-0375-0000
400	400	80	80	170	0,7	1,6	270-0400-0000
450	450	80	80	170	0,7	2,1	270-0450-0000
500	500	80	80	170	0,7	2,3	270-0500-0000
75	50	40	40	135	0,6	0,2	271-0075-0000

Suitable for Hose I.D. d1	Suitable for Hose I.D. d2	Adapter length I1	Adapter length I2	Total Length I3	Wall Thickness	Weight	Dimensions in Stock
mm	mm	mm	mm	mm	mm	kg/piece	Order No.
80	70	40	40	125	0,6	0,2	271-0080-0000
80	50	40	40	135	0,6	0,2	271-0080-2655
100	80	40	40	140	0,6	0,2	271-0100-0000
100	70	40	40	150	0,6	0,2	271-0100-2660
125	100	40	40	145	0,6	0,3	271-0125-0000
125	80	40	40	175	0,6	0,3	271-0125-2665
150	100	40	40	175	0,6	0,3	271-0150-0000
150	80	40	40	205	0,6	0,4	271-0150-2670
150	125	40	40	145	0,6	0,3	271-0150-2671
200	150	40	40	175	0,6	0,5	271-0200-0000
200	100	40	40	245	0,6	0,6	271-0200-2675
200	125	40	40	215	0,6	0,6	271-0200-2676
250	200	60	40	200	0,6	0,8	271-0250-0000
250	125	60	40	300	0,6	1	271-0250-2680
250	150	60	40	270	0,6	0,9	271-0250-2681
300	200	60	40	265	0,7	1,2	271-0300-0000
300	150	60	40	335	0,7	1,3	271-0300-2685
300	250	60	40	195	0,7	1,3	271-0300-2687

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.1.0



NORCLAMP 212

13.2.0




NORCLAMP 216

13.3.0



NORCLAMP 208

13.4.0



NORCLAMP 211

13.5.0



NORCLAMP 212 EC

13.6.0




NORCLAMP 217

13.7.0



NORCLAMP 213

13.14.0



NORCONNECT 223