



Sealing clamp for watertight attachment of heavy, externally corrugated spiral hoses

Properties

- leak-proof and firmly clamping with special spiral geometry
- easily and quickly fitted
- re-usable (threaded)
- rust-proof
- very robust
- conform to RoHS guideline

Design, material

1. clamp band: W2 stainless steel 1.4016 = AISI 430
 clamp wire: stainless steel 1.4310 / AISI 301 / W2 (INOX)
2. screw: chromated steel
 housing: W2 stainless steel 1.4016

Suitable for Hose


AIRDUC®: 355+356, INOX 355+356 MHF-AS, 355+356 EC, 355+356 MHF, INOX 355+356 MHF
 AIRDUC®: HT-PUR 355+356
 TIMBERDUC®: 534 SE

Suitable for Hose	AIRDUC® 345, 355, 534, AIRDUC® 356 ≥ 50 mm	AIRDUC® 356 < 50 mm
I.D. mm	Order No.	Order No.
32	216-0032-2872	216-0032-2010
38	216-0038-2872	216-0038-2010
40	216-0040-2872	216-0040-2010
45	216-0045-2872	216-0045-2010
50	216-0050-0000	-
55	216-0055-0000	-
60	216-0060-0000	-
65	216-0065-0000	-
70	216-0070-0000	-
75	216-0075-0000	-
80	216-0080-0000	-
90	216-0090-0000	-
100	216-0100-0000	-
102	216-0102-0000	-
110	216-0110-0000	-
115	216-0115-0000	-
120	216-0120-0000	-
125	216-0125-0000	-
127	216-0127-0000	-
130	216-0130-0000	-
140	216-0140-0000	-
150	216-0150-0000	-
152	216-0152-0000	-
160	216-0160-0000	-
175	216-0175-0000	-
180	216-0180-0000	-
200	216-0200-0000	-
225	216-0225-0000	-
250	216-0250-0000	-
275	216-0275-0000	-
300	216-0300-0000	-

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.18.0



NORCONNECT 270-271