



**Spiral clamp with quick-release closure for attaching externally corrugated spiral hoses**

**Properties**

- practically leak-proof and firmly clamping with special bridge geometry
- easily and quickly fitted
- re-usable (threaded)
- rust-proof
- very robust
- conform to RoHS guideline

**Design, material**

1. clamp band: W2 stainless steel 1.4016 = AISI 430
2. closure: stainless steel (INOX)
3. bridge: stainless steel 1.4301/ AISI 304/ W2 (INOX)


**Suitable for Hose**

PROTAPE®: 301, 310, 320, 322 EC, 326 MEMORY, 327 MEMORY, 330 MHF, INOX 330 MHF-AS, INOX 330 MHF  
 AIRDUC®: 341+343+345, 350-355 MHF, HT-PUR 351+355, INOX 351+355 MHF, INOX 351+355 MHF-AS, 351+355 EC, 353+355, 362 EC, 362 F  
 TIMBERDUC®: 531+533+534 SE  
 CP: 450, 450+461 PROTECT, 455 MHF, 457, 459 EC, 460, 461, INOX 471+472+475 EC+475 F, HiTex 480-487

Suitable for Hose I.D.	Band Width	Dimensions in Stock
mm	mm	Order No.
70	9	213-0070-0000
75	9	213-0075-0000
80	9	213-0080-0000
90	9	213-0090-0000
100	9	213-0100-0000
110	9	213-0110-0000
115	9	213-0115-0000
120	9	213-0120-0000
125	9	213-0125-0000
130	9	213-0130-0000
140	9	213-0140-0000
150	9	213-0150-0000
160	9	213-0160-0000
175	9	213-0175-0000
180	9	213-0180-0000
200	9	213-0200-0000

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on [www.norres.com](http://www.norres.com).

**Accessories**



13.18.0

NORCONNECT 270-271