



Soft sleeve for SuperFlex hoses

Properties

- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- easily and quickly fitted
- re-usable (threaded)
- conform to RoHS guideline

Temperature Range

- -20 °C approx. to +70 °C approx.
- short time to +80 °C approx.

Design, material

wall: high grade soft PVC

Delivery variants

- black (standard)
- as a pre-assembled hose system with a suitable hose

Suitable for Hose

SuperFlex: PVC 372

Recommended Adapter Ø	Recommended Adapter Length	Threading depth		Total Length	Weight	Suitable for Hose		Dimensions in Stock
		Hose	Hose			I.D.	I.D.	
mm	mm	mm	mm	mm	kg/piece	mm	mm	mm
25	50	45	45	45	0,05	25	25	226-0025-0000
32	50	45	45	45	0,06	32	32	226-0032-0000
38	50	45	45	45	0,07	38	38	226-0038-0000
41	50	45	45	45	0,07	41	41	226-0041-0000
44	50	45	45	45	0,08	44	44	226-0044-0000
51	50	45	45	45	0,09	51	51	226-0051-0000
63	50	45	45	45	0,13	63	63	226-0063-0000
70	45	45	45	45	0,15	70	70	226-0070-0000
76	45	45	45	45	0,17	76	76	226-0076-0000

Other diameters available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.