



Pressure Hose; Hose without reinforcement, smooth interior and exterior

Applications: Pressure hose, especially suitable:
 • for gaseous and liquid media

Properties

- highly flexible
- smooth interior and exterior
- cadmium free
- good resistance to alkalis and acids
- good resistance to chemicals

- good resistance to UV and ozone
- small bending radius
- gas and liquid tight
- crush-proof
- conform to RoHS guideline

Temperature Range

- -20 °C approx. to +60 °C approx.

Design, material

NORFLEX® design

- 1. wall interior and exterior smooth
- wall: soft PVC

Delivery variants

- transparent (standard)
- special colours: full coloured
- customer-specific product marking

I.D.		Wall Thickness	O.D.	Weight	Stock Lengths	Order No.
Inches	mm	mm	mm	kg/m	m	
-	2	1	4	0,012	100	400-9020-0000
1/8"	3	1	5	0,016	100	400-9030-0000
-	4	1	6	0,020	100	400-9040-0000
-	4	1,5	7	0,034	100	400-9040-2182
-	5	1,5	8	0,040	100	400-9050-0000
1/4"	6	1,5	9	0,046	100	400-9060-0000
1/4"	6	2	10	0,065	100	400-9060-2184
-	7	1,5	10	0,052	100	400-9070-0000
5/16"	8	2	12	0,082	50	400-9080-0000
-	9	2	13	0,090	50	400-9090-0000
3/8"	10	2	14	0,098	50	400-9100-0000
-	12	2,5	17	0,148	50	400-9120-0000
-	14	2,5	19	0,168	50	400-9140-0000
-	15	2,5	20	0,178	50	400-9150-0000
5/8"	16	3	22	0,233	50	400-9160-0000
-	18	3	24	0,257	50	400-9180-0000
-	20	2	24	0,180	50	400-9200-0000
-	20	3	26	0,282	50	400-9250-2175
7/8"	22	3	28	0,306	50	400-9220-0000
1"	25	3	31	0,343	25	400-9250-0000
1 1/8"	30	3,5	37	0,479	25	400-9300-0000
1 1/4"	32	4	40	0,588	25	400-9320-0000
1 1/2"	38	5	48	0,878	25	400-9380-0000
-	40	4	48	0,719	25	400-9400-0000
-	40	5	50	0,919	25	400-9400-2187
2"	50	5	60	1,123	25	400-9500-0000
2 3/8"	60	5	70	1,327	25	400-9600-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.3.0



NORCLAMP 208

20120214