



For supplying coolant or air; Flexible, retaining any adjusted position, with threaded connector

Properties

- flexible
- good resistance to alkalis and acids
- good resistance to chemicals (further information on www.norres.com)
- good resistance to UV and ozone
- kink-proof
- retaining any adjusted position
- very robust

- conform to RoHS guideline

Temperature Range

- -20 °C approx. to +70 °C approx.

Design, material

1. rugged and non-corroding connecting thread (brass)
2. wide flat

3. long-life adjustable steel hose (nickel-plated)
4. sealing inner tube
5. robust steel drain spout

Delivery variants

- cut lengths and special lengths
- stop cock
- other accessories on www.norres.com

Connecting Thread	Nominal- Length	Length of Thread	Wrench Size across Flats	I.D.	Bending Radius	Weight	Coolant hose Order No.
mm	mm	mm	mm	mm	mm	kg/m	
R 1/8	200	9	17	3	50	0,080	950-0200-1210
R 1/8	250	9	17	3	50	0,100	950-0250-1210
R 1/8	320	9	17	3	50	0,120	950-0320-1210
R 1/8	400	9	17	3	50	0,150	950-0400-1210
R 1/8	500	9	17	3	50	0,190	950-0500-1210
R 1/8	630	9	17	3	50	0,240	950-0630-1210
R 1/8	800	9	17	3	50	0,300	950-0800-1210
R 1/4	200	9	19	5,5	60	0,120	951-0200-1210
R 1/4	250	9	19	5,5	60	0,150	951-0250-1210
R 1/4	320	9	19	5,5	60	0,180	951-0320-1210
R 1/4	400	9	19	5,5	60	0,230	951-0400-1210
R 1/4	500	9	19	5,5	60	0,280	951-0500-1210
R 1/4	630	9	19	5,5	60	0,350	951-0630-1210
R 1/4	800	9	19	5,5	60	0,450	951-0800-1210
R 3/8	200	9	22	7	70	0,180	952-0200-1210
R 3/8	250	9	22	7	70	0,220	952-0250-1210
R 3/8	320	9	22	7	70	0,280	952-0320-1210
R 3/8	400	9	22	7	70	0,350	952-0400-1210
R 3/8	500	9	22	7	70	0,430	952-0500-1210
R 3/8	630	9	22	7	70	0,540	952-0630-1210
R 3/8	800	9	22	7	70	0,680	952-0800-1210
R 1/2	320	9	24	8	75	0,330	953-0320-1210
R 1/2	400	9	24	8	75	0,400	953-0400-1210
R 1/2	500	9	24	8	75	0,500	953-0500-1210
R 1/2	630	9	24	8	75	0,620	953-0630-1210
R 1/2	800	9	24	8	75	0,780	953-0800-1210

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.