



**Antistatic suction hose; EVA <math> < 10^{11} \Omega</math>, light, crush-proof, lightweight**

**Applications:** Antistatic suction hose, especially suitable:

- in areas liable to contain explosive mixtures (explosion protection)
- for domestic and industrial vacuum cleaners

**Properties**

- surface resistance <math> < 10^{11} \Omega</math>
- light model
- highly flexible
- good resistance to alkalis and acids

- good resistance to UV and ozone
- gas and liquid tight
- crush-proof
- floatable
- light weight
- conform to RoHS guideline

**Temperature Range**

- -25 °C approx. to +65 °C approx.

**Design, material**

1. self-supporting profile design
2. open profile geometry  
wall: EVA

**Delivery variants**

- black (standard)
- as a pre-assembled hose system with NORCONNECT connectors
- customised connectors

I.D.	O.D.	Rec. operating limits	Bending	Weight	Stock Lengths	Further Production Lengths	Order No.
mm	mm	Vacuum bar	Radius mm	kg/m	m	m	
20	26,8	0,500	52	0,130	-	30	373-0020-1002
25	32,2	0,500	66	0,150	30	-	373-0025-1002
30	38	0,500	77	0,200	-	30	373-0030-1002
32	40,4	0,500	82	0,240	30	-	373-0032-1002
35	43,8	0,500	88	0,260	30	-	373-0035-1002
38	47,2	0,500	93	0,310	30	-	373-0038-1002
40	49,4	0,500	100	0,320	30	-	373-0040-1002
45	55	0,500	111	0,370	30	-	373-0045-1002
50	60,4	0,500	122	0,440	30	-	373-0050-1002
60	72	0,500	143	0,670	30	-	373-0060-1002

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on [www.norres.com](http://www.norres.com).

**Accessories**

13.3.0



NORCLAMP 208

13.17.0



NORCONNECT 227