



Pressure hose for the food and pharmaceutical industries (FDA); PTFE-hose without reinforcement, smooth interior and exterior

Applications: Pressure hose, especially suitable:
• for solids
• for gaseous and liquid media

Properties
• highly flexible
• smooth interior and exterior
• food grade wall, complies with: FDA 21 CFR Part 177.2600 / BGW
• odourless and tasteless

- anti-adhesive
- microbe and hydrolysis resistant
- good resistance to alkalis and acids
- extremely good resistance to chemicals
- small bending radius
- free of softener and halogen
- gas and liquid tight
- pressure resistant
- conform to RoHS guideline

Temperature Range
• -150 °C approx. to +200 °C approx.

smooth interior and exterior
NORFLEX® design
1. smooth interior and exterior wall: PTFE

Delivery variants
• transparent (standard)

I.D.		Wall Thickness	O.D.	Rec. operating limits	Weight	Dimensions	Order No.
Inches	mm	mm	mm	Overpressure bar	kg/m	Lengths m	
-	2	1	4	15	0,009	50	407-9020-0000
1/8"	3	1	5	15	0,013	50	407-9030-0000
-	4	1	6	10	0,017	50	407-9040-0000
1/4"	6	1	8	10	0,022	50	407-9060-0000
5/16"	8	1	10	5	0,028	50	407-9080-0000
3/8"	10	1	12	5	0,035	50	407-9100-0000
-	12	1	14	5	0,041	50	407-9120-0000
-	14	1	16	5	0,047	50	407-9140-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.3.0



NORCLAMP 208