



Pressure hose for the food and pharmaceutical industries (FDA); SIL-hose without reinforcement, smooth interior and exterior

Applications: Pressure hose, especially suitable:

- for solids
- for gaseous and liquid media

Properties

- highly flexible
- smooth interior and exterior
- food grade wall, complies with: FDA 21 CFR Part 177.2600 / BGW

- small bending radius
- gas and liquid tight
- crush-proof
- conform to RoHS guideline

Temperature Range

- -60 °C approx. to +180 °C approx.

Design, material

NORFLEX® design

1. wall interior and exterior smooth
wall: silicone 60 ± 5 Shore A

Delivery variants

- transparent (standard)
- special colours: full coloured
- customised product marking

I.D.		Wall Thickness		O.D.	Weight	Stock Lengths	Order No.
Inches	mm	mm	mm	mm	kg/m	m	
-	2	1	4	0,011	50	408-9020-0000	
-	2	2	6	0,030	50	408-9020-2163	
1/8"	3	1	5	0,015	50	408-9030-0000	
1/8"	3	2	7	0,037	50	408-9030-2163	
1/8"	3	1,5	6	0,025	50	408-9030-2182	
-	4	1	6	0,019	50	408-9040-0000	
-	4	2	8	0,045	50	408-9040-2163	
-	4	1,5	7	0,031	50	408-9040-2182	
-	5	1	7	0,022	50	408-9050-0000	
-	5	1,5	8	0,036	50	408-9050-2182	
1/4"	6	1,5	9	0,042	50	408-9060-0000	
1/4"	6	2	10	0,059	50	408-9060-2163	
-	7	1,5	10	0,047	50	408-9070-0000	
5/16"	8	1	10	0,033	50	408-9080-0000	
5/16"	8	2	12	0,074	50	408-9080-2163	
5/16"	8	3	14	0,111	50	408-9080-2175	
-	9	2	13	0,082	50	408-9090-0000	
3/8"	10	2	14	0,089	50	408-9100-0000	
3/8"	10	2,5	15	0,111	50	408-9100-2174	
-	12	2	16	0,104	50	408-9120-0000	
-	12	3	18	0,167	25	408-9120-2175	
-	15	3	21	0,200	25	408-9150-0000	
5/8"	16	3	22	0,211	25	408-9160-0000	
-	20	3	26	0,266	25	408-9200-0000	
1"	25	3	31	0,311	25	408-9250-0000	

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.3.0



NORCLAMP 208