

CONNECT KAMLOK ALU 253



Kamlok coupling

Applications

- silos and tankers: silo charging, silo discharging
- for conveying of dry media and liquids

Properties

- fluted nozzle for band clamp fitting
- Not to be used for explosive fluids group 1 and not according to pressure equipment directive

- REACH according to --> Technology / Technical Information / REACH

Design

- material: aluminium

Size	Weight	Suitable for Hose I.D.	Order No.
(mm)	(kg/pcs)	(mm)	
replacement seal NBR back			
50	0,018	-	253-0050-8068
100	0,034	-	253-0100-8068
female part, type C, suitable for CONNECT 229 CLAMP ASSEMBLY			
50	0,44	51	253-0050-8212
80	0,93	76	253-0075-8212
100	1,29	102	253-0100-8212
male part, type E, suitable for CONNECT 229 CLAMP ASSEMBLY			
50	0,38	51	253-0050-8412
80	0,67	76	253-0075-8412
100	1,05	102	253-0100-8412
-	-	-	-

Accessories



CLAMP 211

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.