



Crush resistant exhaust gas hose

Applications

- flexible hose/ ducting for hot gases
- vehicle/ car gas exhaust system, gas extraction: hose reel, slotted floor channel, underfloor extraction system
- engine test bench, exhaust gas measurement

Properties

- fabric reinforced
- highly flexible + compressible
- protected, flow-optimizing exterior folds
- vibration resistant

- crush resistant
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- exhaust gas temperatures to 390 °F *
- * when correctly applied with exhaust gas funnels and sufficient fresh air supply (50% approximate).

Design

- PROTAPE® tape hose

- special plastic-profile supporting spiral
- fabric-reinforced tape
- wall: EPDM/ PP coated fabric
- wall thickness 0.015 in approx.

Delivery variants

- further diameters and lengths available on request
- black (standard)
- special colors: colored spiral
- customer-specific branding

I.D.	outer Ø	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
2 / 50-51	2.677	11.812	1.890	0.255	25 50	-	326-0051-0000
2,5 / 63-65	3.150	8.268	2.087	0.323	25 50	-	326-0063-0000
3 / 75-76	3.661	5.020	2.362	0.363	25 50	15 20 30 40	326-0076-0000
4 / 100-102	4.685	1.477	2.795	0.477	25 50	15 20 30 40	326-0102-0000
5 / 125-127	5.669	1.034	3.937	0.585	25 50	15 20 30 40	326-0127-0000
6 / 150-152	6.654	0.886	4.331	0.699	25 50	15 20 30 40	326-0152-0000
8 / 200-203	8.661	0.295	6.102	0.921	25	15 20 30	326-0203-0000

Accessories



CONNECT 228



CLAMP 217



CONNECT 270-271



CLAMP 213



CLAMP 212