



Sweeper hose, heavy duty and reinforced, interior folds

Applications

- municipal vehicle: sweeper, sweeping machine

Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- REACH according to --> Technology / Technical Information / REACH

- very good low temperature flexibility
- conforms to RoHS guideline

Temperature range

- -40°F to 195°F

Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall

- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 0.06 to 0.07 in approx.
- reinforcement of the primary abrasion areas

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colors: transparent, partially colored, completely colored
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(psi)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
8 / 200-203	8.465	5.294	3.691	7.008	1.781	12 25	-	355-0203-5015
- / 208	8.661	5.221	3.544	7.165	1.841	-	12 25	355-0208-5015
12 / 305	12.598	3.699	1.772	10.315	3.427	12 25	-	355-0305-5015

Accessories



CONNECT 240 + 241 AS



CONNECT 270-271



CLAMP 211