





Vacuum cleaner hose

Applications

- flexible hose/ ducting for gases and for dust, powder, fibers
- industrial vacuum cleaners, vacuum cleaners
- · swimming pool cleaning
- scrubber, floor cleaning machine

Properties

· light weight

- highly flexible
- · crush resistant
- floatable
- good resistance to alkalis and acids
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

• -50°F to 150°F

Design

- EVA design
- self-supporting profile design
- open profile geometry
- wall: EVA

Delivery variants

- further diameters and lengths available on request
- gray (standard)

I.D.	outer Ø	Vacuum	Bending radius	Weight	Dimensions in Stock	Production lengths	Order No.
(in / mm)	(in)	(inHG)	(in)	(lb/ft)	(ft)	(ft)	
- / 20	1.055	14.765	1.654	0.087	-	100	373-0020-0000
1 / 25	1.268	14.765	2.126	0.101	-	100	373-0025-0000
-/30	1.496	14.765	2.441	0.134	-	100	373-0030-0000
1,25 / 32	1.591	14.765	2.598	0.161	100	-	373-0032-0000
1,36 / 35	1.724	14.765	2.795	0.175	-	100	373-0035-0000
1,5 / 38	1.858	14.765	2.913	0.208	100	-	373-0038-0000
- / 40	1.945	14.765	3.150	0.215	-	100	373-0040-0000
1,75 / 44-45	2.165	14.765	3.504	0.249	100	-	373-0045-0000
2 / 50-51	2.378	14.765	3.819	0.296	100	-	373-0050-0000
2,36 / 60	2.835	14.765	4.449	0.450	-	100	373-0060-0000

Accessories



CONNECT 228



CONNECT 227



CLAMP 208