



PVC hose, heavy

Applications

- flexible hose/ ducting for liquids and for powder, bulk material, granulate and for gases
- airport, airplane, rail vehicle, train, railway, boat, ship/ vessel, yacht: toilet discharging/ disposal
- agricultural industry: irrigation, fertilizers, insecticides
- caravan/ trailer, mobile home/ camper/ RV, boat, ship/ vessel, yachts: sanitary installation, water supply

Properties

- heavy duty
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH
- In compliance with Regulation (EU) No. 10/2011 for simulants A, B, C

Temperature Range

- 10°C to 60°C

Design

- Full plastic hose

- hard plastic spiral integrated in wall
- spiral: rigid PVC
- smooth interior
- wall: soft PVC

Delivery variants

- further diameters and lengths available on request
- green-transparent (standard)
- special colours: coloured spiral, full coloured
- customer-specific branding

| I.D. | outer Ø | Vacuum | Operating pressure (20°C) | Bending Radius | Weight | Dimensions in Stock | Production Lengths | Order No. |
|-----------|---------|--------|---------------------------|----------------|--------|---------------------|--------------------|---------------|
| (in / mm) | (mm) | (bar) | (bar) | (mm) | (kg/m) | (m) | (m) | |
| 1 / 25 | 30.60 | 0,589 | 6,000 | 130.00 | 0.25 | 50 | 25 | 380-0025-8000 |
| 3 / 75-76 | 85.00 | 0,491 | 4,000 | 530.00 | 1.15 | 50 | - | 380-0076-8000 |

Accessories



CLAMP 208



CLAMP 211