CONNECT 685



Adapter for the drillholes with a diameter of 1.77 in

Applications

- membrane tube diffusor, for industrial and municipal wastewater treatment plant, pressure diffusion with fine bubbles, oxygen input for nitrication in activation basins, permanent and intermittend ventilation
- oxygen input and circulation in xed-bed and bioreactors, thorough mixing of activation basins, sand trap louvre ventilation, renaturation of lakes and rivers, aquacultures, sh farming

Properties

• conforms to RoHS guideline

I.D.	outer Ø	Weight	Order No.
(mm)	(in)	(Ib/pcs)	
1.535	1.732	0.007	685-0045-2762


Accessories



CONNECT 681



CLAMP 682



CONNECT 684



CONNECT 683

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at <u>www.norres.com/us/technology</u>. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimatives of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.