

METAL HOSE Agraff VA 150



Non-rusting and highly exible metal protection conduit; extremely robust; double folded metal prole

Applications

- cable protection: cable protection conduit, cable protection tube, cable protection hose, electric installation, switch cabinets, switch cabinet installation, cable harnessing/ cable assembly

Properties

- IP 40 to EN/ IEC 60529
- good screening factor (EMC)

- highly flexible
- increased resistance to tear, pressure and impact
- conforms to RoHS guideline

Temperature range

- up to 1.100 °F

Design

- Metal hose
- profiled metal strip, stainless steel (INOX)
- twice rolled profile

Delivery variants

- further diameters and lengths available on request

Nominal width connecting part (in)	I.D. (mm)	outer Ø (in)	Bending radius (middle of hose) (in)	Weight (lb/ft)	PU (ft)	Order No.
PU: 10						
0.276	0.197	0.276	1.378	0.067	32.810	150-3007-9010
0.315	0.236	0.315	1.575	0.081	32.810	150-3008-9010
0.394	0.315	0.394	1.772	0.087	32.810	150-3010-9010
0.551	0.433	0.551	1.969	0.094	32.810	150-3014-9010
0.669	0.551	0.669	2.362	0.175	32.810	150-3017-9010
0.748	0.630	0.748	2.559	0.195	32.810	150-3019-9010
0.827	0.709	0.827	2.756	0.208	32.810	150-3021-9010
1.063	0.906	1.063	3.543	0.269	32.810	150-3027-9010
1.417	1.260	1.417	5.315	0.497	32.810	150-3036-9010
PU: 50						
0.276	0.197	0.276	1.378	0.067	164.050	150-3007-9050
0.315	0.236	0.315	1.575	0.081	164.050	150-3008-9050
0.394	0.315	0.394	1.772	0.087	164.050	150-3010-9050
0.551	0.433	0.551	1.969	0.094	164.050	150-3014-9050
0.669	0.551	0.669	2.362	0.175	164.050	150-3017-9050
0.748	0.630	0.748	2.559	0.195	164.050	150-3019-9050
0.827	0.709	0.827	2.756	0.208	164.050	150-3021-9050
1.063	0.906	1.063	3.543	0.269	164.050	150-3027-9050
PU: 25						
1.417	1.260	1.417	5.315	0.497	82.025	150-3036-9025

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

METAL HOSE Agraff VA 150

Accessories



GM 164



GK 169



AU 159