

CONNECT 205





Connectors for connecting or attaching metal hoses

Properties
- conforms to RoHS guideline

- Flange 205: cylindrical adapter with rotatable flange, extension at one end for attaching the metal hose
- REACH according to --> Technology / Technical Information / REACH

Design
- Stainless Steel (INOX)

Delivery variants
- further diameters available on request

No. + Ø Fixing Holes	S	B	K	D1	A	L	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
Assembly; (please select the hose separately); rivetting									
-	-	-	-	-	-	-	-	-	205-0000-2905
Flange 205 Stainless Steel (INOX)									
4x9,5	1,00	6	89	115	40	70	0,480	50	205-0050-1100
4x9,5	1,00	6	99	125	40	80	0,550	60	205-0060-1100
4x9,5	1,00	6	110	133	40	80	0,610	70	205-0070-1100
4x9,5	1,00	6	118	142	40	80	0,670	80	205-0080-1100
4x9,5	1,00	6	139	162	50	100	0,870	100	205-0100-1100
4x9,5	1,00	6	165	187	50	100	1,030	120	205-0120-1100
4x9,5	1,00	6	165	187	50	100	1,040	125	205-0125-1100
8x11,5	1,00	6	182	212	60	120	1,340	140	205-0140-1100
8x11,5	1,25	6	219	252	60	120	1,830	180	205-0180-1100
8x11,5	1,25	6	241	273	60	130	2,100	200	205-0200-1100
8x11,5	1,25	6	292	323	60	130	2,580	250	205-0250-1100
8x11,5	1,50	6	349	383	60	140	4,480	300	205-0300-1100

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.