

# CLAMP 211



T-bolt clamp for attaching heavy-duty hoses with a smooth exterior surface

## Properties

- easily and quickly fitted
- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Design

- Quality: W1; Clamp strip + screw: galvanised steel
- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Screw: galvanised steel
- Quality: W4; Clamp strip + screw: stainless steel 1.4301 = AISI 304

suitable for hose Ø-outside (mm)	Clamping range (in)	Band width (in)	PU (Pcs)	Order No.
<b>W1</b>				
17-19	0.669	0.709	1	211-0021-0000
20-22	0.787	0.709	1	211-0023-0000
23-25	0.906	0.709	1	211-0025-0000
26-28	1.024	0.709	1	211-0029-0000
29-31	1.142	0.709	1	211-0031-0000
31-34	1.220	0.709	1	211-0034-0000
36-39	1.417	0.709	1	211-0040-0000
40-43	1.575	0.709	1	211-0043-0000
44-47	1.732	0.787	1	211-0047-0000
48-51	1.890	0.787	1	211-0051-0000
52-55	2.047	0.787	1	211-0055-0000
56-59	2.205	0.787	1	211-0059-0000
60-63	2.362	0.787	1	211-0063-0000
64-67	2.520	0.787	1	211-0068-0000
68-73	2.677	0.984	1	211-0073-0000
74-79	2.913	0.984	1	211-0079-0000
80-85	3.150	0.984	1	211-0085-0000
86-91	3.386	0.984	1	211-0091-0000
92-97	3.622	0.984	1	211-0097-0000
98-103	3.858	0.984	1	211-0104-0000
104-112	4.094	0.984	1	211-0112-0000
113-121	4.449	0.984	1	211-0121-0000
122-130	4.803	0.984	1	211-0130-0000
131-139	5.157	1.181	1	211-0140-0000
140-148	5.512	1.181	1	211-0150-0000
149-161	5.866	1.181	1	211-0162-0000
162-174	6.378	1.181	1	211-0174-0000
175-187	6.890	1.181	1	211-0187-0000
188-200	7.402	1.181	1	211-0200-0000
201-213	7.913	1.181	1	211-0213-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at [www.norres.com/us/technology/](http://www.norres.com/us/technology/). NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

# CLAMP 211

suitable for hose Ø-outside (mm)	Clamping range (in)	Band width (in)	PU (Pcs)	Order No.
214-226	8.425	1.181	1	211-0226-0000
227-239	8.937	1.181	1	211-0239-0000
240-252	9.449	1.181	1	211-0252-0000
<b>W2</b>				
17-19	0.669	0.709	1	211-0021-9200
20-22	0.787	0.709	1	211-0023-9200
23-25	0.906	0.709	1	211-0025-9200
26-28	1.024	0.709	1	211-0029-9200
29-31	1.142	0.709	1	211-0031-9200
31-34	1.220	0.709	1	211-0034-9200
36-39	1.417	0.709	1	211-0040-9200
40-43	1.575	0.709	1	211-0043-9200
44-47	1.732	0.787	1	211-0047-9200
48-51	1.890	0.787	1	211-0051-9200
52-55	2.047	0.787	1	211-0055-9200
56-59	2.205	0.787	1	211-0059-9200
60-63	2.362	0.787	1	211-0063-9200
64-67	2.520	0.787	1	211-0068-9200
68-73	2.677	0.984	1	211-0073-9200
74-79	2.913	0.984	1	211-0079-9200
80-85	3.150	0.984	1	211-0085-9200
86-91	3.386	0.984	1	211-0091-9200
92-97	3.622	0.984	1	211-0097-9200
98-103	3.858	0.984	1	211-0104-9200
104-112	4.094	0.984	1	211-0112-9200
113-121	4.449	0.984	1	211-0121-9200
122-130	4.803	0.984	1	211-0130-9200
131-139	5.157	1.181	1	211-0140-9200
140-148	5.512	1.181	1	211-0150-9200
149-161	5.866	1.181	1	211-0162-9200
162-174	6.378	1.181	1	211-0174-9200
175-187	6.890	1.181	1	211-0187-9200
188-200	7.402	1.181	1	211-0200-9200
201-213	7.913	1.181	1	211-0213-9200
214-226	8.425	1.181	1	211-0226-9200
227-239	8.937	1.181	1	211-0239-9200
240-252	9.449	1.181	1	211-0252-9200
<b>W4</b>				
26-28	1.024	0.709	1	211-0029-9230
29-31	1.142	0.709	1	211-0031-9230
31-34	1.220	0.709	1	211-0034-9230
36-39	1.417	0.709	1	211-0040-9230
44-47	1.732	0.787	1	211-0047-9230
48-51	1.890	0.787	1	211-0051-9230
52-55	2.047	0.787	1	211-0055-9230
56-59	2.205	0.787	1	211-0059-9230
60-63	2.362	0.787	1	211-0063-9230
64-67	2.520	0.787	1	211-0068-9230
68-73	2.677	0.984	1	211-0073-9230
74-79	2.913	0.984	1	211-0079-9230
80-85	3.150	0.984	1	211-0085-9230

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at [www.norres.com/us/technology/](http://www.norres.com/us/technology/). NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

## CLAMP 211

suitable for hose Ø-outside (mm)	Clamping range (in)	Band width (in)	PU (Pcs)	Order No.
86-91	3.386	0.984	1	211-0091-9230
92-97	3.622	0.984	1	211-0097-9230
98-103	3.858	0.984	1	211-0104-9230
104-112	4.094	0.984	1	211-0112-9230
113-121	4.449	0.984	1	211-0121-9230
122-130	4.803	0.984	1	211-0130-9230
131-139	5.157	1.181	1	211-0140-9230
140-148	5.512	1.181	1	211-0150-9230
149-161	5.866	1.181	1	211-0162-9230
162-174	6.378	1.181	1	211-0174-9230
175-187	6.890	1.181	1	211-0187-9230
188-200	7.402	1.181	1	211-0200-9230
201-213	7.913	1.181	1	211-0213-9230
214-226	8.425	1.181	1	211-0226-9230
227-239	8.937	1.181	1	211-0239-9230
240-252	9.449	1.181	1	211-0252-9230

## Accessories



CONNECT 270-271