

CLAMP 213



Bridge Clamp with quick-release closure
for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Clamp wire: stainless steel 1.4310 = AISI 301 (INOX); Screw: stainless steel 1.4301 = AISI 304; Body: stainless steel 1.4016 = AISI 430

Delivery variants

- further diameters available on request

Suitable for Hose I.D. (mm)	Band Width (mm)	Order No.
60	9	213-0060-0000
70	9	213-0070-0000
75	9	213-0075-0000
80	9	213-0080-0000
90	9	213-0090-0000
100	9	213-0100-0000
110	9	213-0110-0000
115	9	213-0115-0000
120	9	213-0120-0000
125	9	213-0125-0000
130	9	213-0130-0000
140	9	213-0140-0000
150	9	213-0150-0000
160	9	213-0160-0000
175	9	213-0175-0000
180	9	213-0180-0000
200	9	213-0200-0000

Accessories



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.