

CLAMP 213



Bridge Clamp with quick-release closure for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted

Design

- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Clamp wire: stainless steel 1.4310 = AISI 301 (INOX); Screw: stainless steel 1.4301 = AISI 304; Body: stainless steel 1.4016 = AISI 430

Delivery variants

- further diameters available on request

Suitable for hose I.D.	Band width	Order No.
(in)	(in)	
60	0.354	213-0060-0000
70	0.354	213-0070-0000
75	0.354	213-0075-0000
80	0.354	213-0080-0000
90	0.354	213-0090-0000
100	0.354	213-0100-0000
110	0.354	213-0110-0000
115	0.354	213-0115-0000
120	0.354	213-0120-0000
125	0.354	213-0125-0000
130	0.354	213-0130-0000
140	0.354	213-0140-0000
150	0.354	213-0150-0000
160	0.354	213-0160-0000
175	0.354	213-0175-0000
180	0.354	213-0180-0000
200	0.354	213-0200-0000

Accessories



CONNECT 270-271

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.