

# CLAMP 217



Bridge clamp with eyelet for attaching externally corrugated spiral hoses

## Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted

## Design

- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Design

- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; Screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; Bridge: stainless steel 1.4301 = AISI 304 (INOX); Fixing eyelet: galvanised steel

## Delivery variants

- further diameters available on request

Suitable for Hose I.D.	Clamping Range	Band Width	Order No.
(mm)	(mm)	(mm)	
60-65	55-75	9	217-0055-0000
70-75	65-85	9	217-0065-0000
90-95	85-105	9	217-0085-0000
100-105	95-115	9	217-0095-0000
120-127	115-135	9	217-0115-0000
130-135	125-145	9	217-0125-0000
140-145	135-155	9	217-0135-0000
150-155	145-165	9	217-0145-0000
160-165	155-175	9	217-0155-0000
170-175	165-185	9	217-0165-0000
180-185	175-195	9	217-0175-0000
200-205	195-215	9	217-0195-0000
220-225	215-235	12	217-0215-0000
250-255	245-265	12	217-0245-0000
280-285	275-295	12	217-0275-0000
300-305	295-315	12	217-0295-0000
320-325	315-355	12	217-0315-0000
500-505	495-515	12	217-0495-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).