

# CONNECT 223



Shrink sleeve for connecting one hose to another or to an adapter

## Properties

- adapts itself to any surface
- easily and quickly fitted
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

## Temperature Range

- -40° C to 125° C

## Design

- polyolefine

## Delivery variants

- further diameters available on request
- black (standard)

Shrinking Range	Total Length	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	
15-30	70	15-22	223-0038-0000
22-50	80	20-40	223-0050-0000
25-63	80	30-50	223-0063-0000
30-75	90	40-60	223-0075-0000
35-85	100	50-70	223-0085-0000
40-95	110	60-80	223-0095-0000
45-115	120	80-100	223-0115-0000
50-140	150	100-130	223-0140-0000
60-160	170	130-150	223-0160-0000
70-180	190	150-170	223-0180-0000

## Sleeve length: 1m

15-30	1000	15-22	223-0038-9001
22-50	1000	20-40	223-0050-9001
25-63	1000	30-50	223-0063-9001
30-75	1000	40-60	223-0075-9001
35-85	1000	50-70	223-0085-9001
40-95	1000	60-80	223-0095-9001
45-115	1000	80-100	223-0115-9001
50-140	1000	100-130	223-0140-9001
60-160	1000	130-150	223-0160-9001
70-180	1000	150-170	223-0180-9001

## Accessories



Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).

