CONNECT 226



Soft sleeve for SuperFlex hoses

Applications

• industrial vacuum cleaners, vacuum cleaners

Properties

- · easily and quickly fitted
- re-usable (threaded version)
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5°F to 160°F
- short time to 175°F

Design

• wall: high grade soft PVC

Delivery variants

- further diameters available on request
- black (standard)

Rec. adapter Ø	Rec. adapter length	Threading depth hose	Total Length	Weight	Suitable for hose I.D.	Order No.
(in)	(in)	(in)	(in)	(lb/pcs)	(in)	
		Suit	able for hose 372	0000		
0.984	1.969	1.772	3.937	0.110	25	226-0025-0000
1.260	1.969	1.772	3.937	0.132	32	226-0032-0000
1.496	1.969	1.772	3.937	0.154	38	226-0038-0000
1.614	1.969	1.772	3.937	0.154	41	226-0041-0000
1.732	1.969	1.772	3.937	0.176	44	226-0044-0000
2.008	1.969	1.772	3.937	0.198	51	226-0051-0000
2.480	1.969	1.772	3.937	0.287	63	226-0063-0000
2.756	1.772	1.772	3.937	0.331	70	226-0070-0000
2.992	1.772	1.772	3.937	0.375	76	226-0076-0000

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate with the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.