



Soft sleeve for EVA hoses

### Applications

- industrial vacuum cleaners, vacuum cleaners

### Properties

- easily and quickly fitted
- re-usable
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -20 °C to 70 °C
- short time to 80 °C

### Design

- Wall: high grade soft PVC, electrically conductive  $<10^6$

### Delivery variants

- further diameters available on request
- black (standard)
- grey (standard)

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
<b>grey</b>						
32	44	40	85	0,060	32	227-0032-0000
38	44	40	85	0,070	38	227-0038-0000
50	49	41	90	0,090	50	227-0050-0000
<b>black</b>						
32	44	40	85	0,060	32	227-0032-0001
38	44	40	85	0,070	38	227-0038-0001
45	44	40	90	0,080	45	227-0045-0001
50	49	41	90	0,090	50	227-0050-0001
<b>Electrically conductive <math>&lt;10^6</math> ; black</b>						
32	44	40	85	0,060	32	227-0032-1003
38	44	40	85	0,070	38	227-0038-1003
50	49	41	90	0,090	50	227-0050-1003

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/).