


CONNECT 227



Soft sleeve for EVA hoses

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -20 °C to 70 °C
- short time to 80 °C

Design

- Wall: high grade soft PVC, electrically conductive 10^6

Delivery variants

- further diameters available on request
- black (standard)
- grey (standard)

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
grey						
32	44	40	85	0,060	32	227-0032-0000
38	44	40	85	0,070	38	227-0038-0000
50	49	41	90	0,090	50	227-0050-0000
black						
32	44	40	85	0,060	32	227-0032-0001
38	44	40	85	0,070	38	227-0038-0001
45	44	40	90	0,080	45	227-0045-0001
50	49	41	90	0,090	50	227-0050-0001
Electrically conductive <math>10^6</math> ; black						
32	44	40	85	0,060	32	227-0032-1003
38	44	40	85	0,070	38	227-0038-1003
50	49	41	90	0,090	50	227-0050-1003

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.