



Soft sleeve for EVA hoses

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5°F to 160°F
- short time to 175°F

Design

- Wall: high grade soft PVC, electrically conductive $<10^6$

Delivery variants

- further diameters available on request
- black (standard)
- gray (standard)

| Rec. adapter Ø (in) | Rec. adapter length (in) | Threading depth hose (in) | Total Length (in) | Weight (lb/pcs) | Suitable for hose I.D. (in) | Order No. |
|---|-----------------------------|------------------------------|----------------------|--------------------|--------------------------------|---------------|
| gray | | | | | | |
| 1.260 | 1.732 | 1.575 | 3.346 | 0.132 | 32 | 227-0032-0000 |
| 1.496 | 1.732 | 1.575 | 3.346 | 0.154 | 38 | 227-0038-0000 |
| 1.969 | 1.929 | 1.614 | 3.543 | 0.198 | 50 | 227-0050-0000 |
| black | | | | | | |
| 1.260 | 1.732 | 1.575 | 3.346 | 0.132 | 32 | 227-0032-0001 |
| 1.496 | 1.732 | 1.575 | 3.346 | 0.154 | 38 | 227-0038-0001 |
| 1.772 | 1.732 | 1.575 | 3.543 | 0.176 | 45 | 227-0045-0001 |
| 1.969 | 1.929 | 1.614 | 3.543 | 0.198 | 50 | 227-0050-0001 |
| Electrically conductive $<10^6$; black | | | | | | |
| 1.260 | 1.732 | 1.575 | 3.346 | 0.132 | 32 | 227-0032-1003 |
| 1.496 | 1.732 | 1.575 | 3.346 | 0.154 | 38 | 227-0038-1003 |
| 1.969 | 1.929 | 1.614 | 3.543 | 0.198 | 50 | 227-0050-1003 |