
CONNECT 227





Soft sleeve for EVA hoses

Applications

• industrial vacuum cleaners, vacuum cleaners

Properties

- · easily and quickly fitted
- re-usable
- · good resistance to alkalis and acids

• good resistance to chemicals

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5°F to 160°F
- short time to 175°F

Design

 Wall: high grade soft PVC, electrically conductive <10⁶

Delivery variants

- further diameters available on request
- black (standard)
- gray (standard)

Rec. adapter length	Threading depth hose	Total Length	Weight	Suitable for hose I.D.	Order No.
(in)	(in)	(in)	(lb/pcs)	(in)	
		gray			
1.732	1.575	3.346	0.132	32	227-0032-0000
1.732	1.575	3.346	0.154	38	227-0038-0000
1.929	1.614	3.543	0.198	50	227-0050-0000
		black			
1.732	1.575	3.346	0.132	32	227-0032-0001
1.732	1.575	3.346	0.154	38	227-0038-0001
1.732	1.575	3.543	0.176	45	227-0045-0001
1.929	1.614	3.543	0.198	50	227-0050-0001
Electrically conductive <10 ⁶ ; black					
1.732	1.575	3.346	0.132	32	227-0032-1003
1.732	1.575	3.346	0.154	38	227-0038-1003
1.929	1.614	3.543	0.198	50	227-0050-1003
	1.732 1.732 1.732 1.732 1.929 1.732 1.732 1.929	adapter length (in) depth hose 1.732 1.575 1.732 1.575 1.929 1.614 1.732 1.575 1.732 1.575 1.732 1.575 1.929 1.614 Electrical Longon (Inc.) 1.732 1.575 1.732 1.575 1.732 1.575 1.732 1.575	adapter length depth hose Length (in) (in) (in) 1.732 1.575 3.346 1.732 1.575 3.346 1.929 1.614 3.543 black 1.732 1.575 3.346 1.732 1.575 3.346 1.732 1.575 3.543 1.929 1.614 3.543 Electrically conductive <106 strong transport	adapter length (in) depth hose Length gray 1.732 1.575 3.346 0.132 1.732 1.575 3.346 0.154 1.929 1.614 3.543 0.198 black 1.732 1.575 3.346 0.132 1.732 1.575 3.346 0.154 1.732 1.575 3.543 0.176 1.929 1.614 3.543 0.198 Electrically conductive <10 ⁶ ; black 1.732 1.575 3.346 0.132 1.732 1.575 3.346 0.132 1.732 1.575 3.346 0.154	adapter length (in) depth hose Length hose I.D. gray 1.732 1.575 3.346 0.132 32 1.732 1.575 3.346 0.154 38 1.929 1.614 3.543 0.198 50 black 1.732 1.575 3.346 0.132 32 1.732 1.575 3.346 0.154 38 1.732 1.575 3.543 0.176 45 1.929 1.614 3.543 0.198 50 Electrically conductive <10°; black 1.732 1.575 3.346 0.132 32 1.732 1.575 3.346 0.132 32 1.732 1.575 3.346 0.132 32 1.732 1.575 3.346 0.154 38