


CONNECT 227



Soft sleeve for EVA hoses

Applications

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -5°F to 160°F
- short time to 175°F

Design

- Wall: high grade soft PVC, electrically conductive 10^6

Delivery variants

- further diameters available on request
- black (standard)
- gray (standard)

Rec. adapter Ø (in)	Rec. adapter length (in)	Threading depth hose (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
gray						
1.260	1.732	1.575	3.346	0.132	32	227-0032-0000
1.496	1.732	1.575	3.346	0.154	38	227-0038-0000
1.969	1.929	1.614	3.543	0.198	50	227-0050-0000
black						
1.260	1.732	1.575	3.346	0.132	32	227-0032-0001
1.496	1.732	1.575	3.346	0.154	38	227-0038-0001
1.772	1.732	1.575	3.543	0.176	45	227-0045-0001
1.969	1.929	1.614	3.543	0.198	50	227-0050-0001
Electrically conductive <math>10^6</math>; black						
1.260	1.732	1.575	3.346	0.132	32	227-0032-1003
1.496	1.732	1.575	3.346	0.154	38	227-0038-1003
1.969	1.929	1.614	3.543	0.198	50	227-0050-1003

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.