CONNECT 240 + 241 FOOD














Soft sleeve to slide onto connectors or push into pipes, foodgrade

Applications

- food industry, pharmaceutical industry: food, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses
- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)

• gas- and liquid-tight as pre-fitted version

- highly abrasion resistant
- Food grade wall, complies with: EU-Directive 10/2011, EC 1935/2004 and EU 2015/174
- odorless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40°F to 195°F
- short time to 255°F

Design

 \bullet wall: special premium ether-polyurethane (Pre-PUR $^{\circledR})$

Delivery variants

- · further diameters available on request
- special colors: full colored

Rec. adapter Ø	Rec. adapter length	Threading depth hose	Total Length	Weight	Suitable for hose I.D.	Order No.				
(in)	(in)	(in)	(in)	(lb/pcs)	(in)					
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345										
1.496	1.732	1.575	3.346	0.187	38	240-0038-0010				
1.575	1.732	1.575	3.346	0.185	40	240-0040-0010				
1.969	1.929	1.614	3.543	0.196	50	240-0050-0010				
2.362	1.929	1.614	3.543	0.265	60	240-0060-0010				
2.756	2.047	1.732	3.937	0.322	70	240-0070-0010				
1.260	1.732	1.575	3.346	0.154	32	241-0032-8600				
2.953	2.362	1.850	4.213	0.441	75	241-0075-8600				
3.150	2.362	2.047	4.409	0.551	80	241-0080-8600				
3.937	2.559	2.244	4.803	0.684	100	241-0100-8600				
4.921	2.953	2.441	5.394	1.058	125	241-0125-8600				
5.906	3.346	2.756	6.102	1.499	150	241-0150-8600				
7.874	3.937	3.150	7.087	2.426	200	241-0200-8600				
9.843	4.134	3.543	7.677	3.308	250	241-0250-8600				
11.811	4.528	3.937	8.465	4.983	300	241-0300-8600				
			pre-fitted							
1.260	1.732	1.575	3.346	0.154	32	241-0032-8550				
1.575	1.732	1.575	3.346	0.176	40	241-0040-8550				
1.969	1.929	1.614	3.543	0.176	50	241-0050-8550				
2.362	1.929	1.614	3.543	0.265	60	241-0060-8550				
3.150	2.362	2.047	4.409	0.551	80	241-0080-8550				
3.937	2.559	2.244	4.803	0.684	100	241-0100-8550				
Threaded; Suitable for Hose 356										
1.575	1.732	1.575	3.346	0.176	40	241-0040-8601				
2.362	1.929	1.614	3.543	0.265	60	241-0060-8601				

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 ° F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and us/technology/. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.

CONNECT 240 + 241 FOOD









Rec. adapter Ø	Rec. adapter length	Threading depth hose	Total Length	Weight	Suitable for hose I.D.	Order No.
(in)	(in)	(in)	(in)	(lb/pcs)	(in)	
2.953	2.362	1.850	4.213	0.441	75	241-0075-8601
3.150	2.362	2.047	4.409	0.551	80	241-0080-8601