



Threaded adapter

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas- and liquid-tight as pre-fitted version
- highly abrasion resistant
- good resistance to oil, gasoline, and chemicals

- thread reference DIN ISO 228
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40 °F to 195 °F

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colors: full colored
- gas- and liquid-tight as pre-fitted version

Thread	Threading depth hose (in)	Thread Length (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
2,00"	1.772	0.937	3.386	0.331	50	242-0050-8500
2,25"	1.772	1.004	3.425	0.397	55	242-0055-8500
2,50"	1.772	1.043	3.504	0.485	65	242-0065-8500
3,00"	1.850	1.173	3.819	0.617	75	242-0075-8500
4,00"	2.008	1.409	4.252	0.992	100	242-0100-8500
5,00"	2.283	1.575	4.803	1.764	125	242-0125-8500
6,00"	2.677	1.575	5.197	2.205	150	242-0150-8500
Threaded; Suitable for Hose 356						
2,00"	1.772	0.937	3.386	0.331	50	242-0050-8501
3,00"	1.850	1.173	3.819	0.617	75	242-0075-8501
4,00"	2.008	1.409	4.252	0.992	100	242-0100-8501
pre-fitted; (please select the hose separately)						
2,00"	1.772	0.937	3.386	0.331	50	242-0050-8551