



CONNECT 242



Threaded adapter

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas- and liquid-tight as pre-fitted version
- highly abrasion resistant
- good resistance to oil, gasoline, and chemicals

- thread reference DIN ISO 228
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40 °F to 195 °F

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colors: full colored
- gas- and liquid-tight as pre-fitted version

Thread	Threading depth hose (in)	Thread Length (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
2,00"	1.772	0.937	3.386	0.331	50	242-0050-8500
2,25"	1.772	1.004	3.425	0.397	55	242-0055-8500
2,50"	1.772	1.043	3.504	0.485	65	242-0065-8500
3,00"	1.850	1.173	3.819	0.617	75	242-0075-8500
4,00"	2.008	1.409	4.252	0.992	100	242-0100-8500
5,00"	2.283	1.575	4.803	1.764	125	242-0125-8500
6,00"	2.677	1.575	5.197	2.205	150	242-0150-8500
Threaded; Suitable for Hose 356						
2,00"	1.772	0.937	3.386	0.331	50	242-0050-8501
3,00"	1.850	1.173	3.819	0.617	75	242-0075-8501
4,00"	2.008	1.409	4.252	0.992	100	242-0100-8501
pre-fitted; (please select the hose separately)						
2,00"	1.772	0.937	3.386	0.331	50	242-0050-8551

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68 °F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.