
CONNECT 243





Flanged pipe according to the popular pipe systems in the ventilation field (for example Jacob-Standard)

Properties
- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range
- -40 °C to 60 °C

Design
- Flanged pipe: galvanised sheet metal
- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants
- further diameters available on request
- black (standard)
- special colours: full coloured
- Stainless Steel (INOX)
- gas and liquid tight as pre-fitted version

Suitable for Ø-Pipe System (mm)	Threading depth Hose (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
80	46	136	0,380	80	243-0080-8500
100	51	141	0,580	100	243-0100-8500
120	58	148	0,870	120	243-0120-8500
150	68	158	1,100	150	243-0150-8500
200	80	170	1,810	200	243-0200-8500
250	90	180	2,700	250	243-0250-8500
300	100	190	3,340	300	243-0300-8500
Threaded; Suitable for Hose 356					
80	46	136	0,380	80	243-0080-8501
100	51	141	0,580	100	243-0100-8501
120	58	148	0,870	120	243-0120-8501
150	68	158	1,100	150	243-0150-8501
200	80	170	1,810	200	243-0200-8501
pre-fitted					
150	68	158	1,100	150	243-0150-8551
200	80	170	1,810	200	243-0200-8551

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.