CONNECT 243





Flanged pipe according to the popular pipe systems in the ventilation field (for example Jacob-Standard)

Properties
- easily and quickly fitted
- re-usable (threaded version)
- gas- and liquid-tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range
- -40°F to 140°F

Design
- Flanged pipe: galvanised sheet metal
- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants
- further diameters available on request
- black (standard)
- special colors: full colored
- stainless steel (INOX)
- gas- and liquid-tight as pre-fitted version

Suitable for Ø-Pipe System (in)	Threading depth hose (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
3.150	1.811	5.354	0.838	80	243-0080-8500
3.937	2.008	5.551	1.279	100	243-0100-8500
4.724	2.283	5.827	1.918	120	243-0120-8500
5.906	2.677	6.220	2.426	150	243-0150-8500
7.874	3.150	6.693	3.991	200	243-0200-8500
9.843	3.543	7.087	5.954	250	243-0250-8500
11.811	3.937	7.480	7.365	300	243-0300-8500
Threaded; Suitable for Hose 356					
3.150	1.811	5.354	0.838	80	243-0080-8501
3.937	2.008	5.551	1.279	100	243-0100-8501
4.724	2.283	5.827	1.918	120	243-0120-8501
5.906	2.677	6.220	2.426	150	243-0150-8501
7.874	3.150	6.693	3.991	200	243-0200-8501
pre-fitted					
5.906	2.677	6.220	2.426	150	243-0150-8551
7.874	3.150	6.693	3.991	200	243-0200-8551

Positive and negative pressure ratings are the recommended maximum operating values. Products can be manufactured to meet higher operating values upon request. The bend radius is calculated from the center of the hose in an arched position. Additional information at www.norres.com/us/technology/. NORRES reserves the right to modify technical data at any time. Technical data based on tests at 68°F and are approx. values. Proper use and maintenance of NORRES hoses is the sole responsibility of purchaser and ultimate user of the product. The individual conditions, applications and the number of variables make firm recommendations technically impossible. This information is intended as a general guide only.