



Flanged pipe according to the popular pipe systems in the ventilation field (for example Jacob-Standard)

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas- and liquid-tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant

- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40 °F to 140 °F

Design

- Flanged pipe: galvanised sheet metal
- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colors: full colored
- stainless steel (INOX)
- gas- and liquid-tight as pre-fitted version

Suitable for Ø-Pipe System (in)	Threading depth hose (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
3.150	1.811	5.354	0.838	80	243-0080-8500
3.937	2.008	5.551	1.279	100	243-0100-8500
4.724	2.283	5.827	1.918	120	243-0120-8500
5.906	2.677	6.220	2.426	150	243-0150-8500
7.874	3.150	6.693	3.991	200	243-0200-8500
9.843	3.543	7.087	5.954	250	243-0250-8500
11.811	3.937	7.480	7.365	300	243-0300-8500
Threaded; Suitable for Hose 356					
3.150	1.811	5.354	0.838	80	243-0080-8501
3.937	2.008	5.551	1.279	100	243-0100-8501
4.724	2.283	5.827	1.918	120	243-0120-8501
5.906	2.677	6.220	2.426	150	243-0150-8501
7.874	3.150	6.693	3.991	200	243-0200-8501
pre-fitted					
5.906	2.677	6.220	2.426	150	243-0150-8551
7.874	3.150	6.693	3.991	200	243-0200-8551