



Flanged pipe according to the popular pipe systems in the ventilation field (for example Jacob-Standard), food-grade

## Applications

- food industry, pharmaceutical industry: food, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses

## Properties

- easily and quickly fitted
- re-usable (threaded version)

- gas- and liquid-tight as pre-fitted version
- highly abrasion resistant
- Food grade wall, complies with: EU-Directive 10/2011, EC 1935/2004 and EU 2015/174
- odorless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

## Temperature range

- -40 °F to 195 °F

## Design

- Flanged pipe: Stainless Steel (INOX)
- wall: special premium ether-polyurethane (Pre-PUR®)

## Delivery variants

- further diameters and lengths available on request
- special colors: full colored

Suitable for Ø-Pipe System (in)	Threading depth hose (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 356					
3.150	1.811	5.354	0.838	80	243-0080-8509
3.937	2.008	5.551	1.279	100	243-0100-8509
7.874	3.150	6.693	3.991	200	243-0200-8509
pre-fitted					
3.150	1.811	5.354	0.838	80	243-0080-8559
3.937	2.008	5.551	1.279	100	243-0100-8559
4.724	2.283	5.827	1.918	120	243-0120-8559
7.874	3.150	6.693	3.991	200	243-0200-8559
9.843	3.543	7.087	5.954	250	243-0250-8559
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
3.150	1.811	5.354	0.838	80	243-0080-8610
3.937	2.008	5.551	1.279	100	243-0100-8610
4.724	2.283	5.827	1.918	120	243-0120-8610
5.906	2.677	6.220	2.426	150	243-0150-8610
7.874	3.150	6.693	3.991	200	243-0200-8610
9.843	3.543	7.087	5.954	250	243-0250-8610