
CONNECT TRI-CLAMP FITTING 245









TRI clamp adapters based on DIN 32676 and ISO 2852

Applications

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- pelleting machines/ tablet presses
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system

Properties

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

• -40°C to 90°C

Design

- fitting: stainless steel 1.4404 (stamped) = AISI 316L
- matching accessories: seal (silicone white, FDA), adapter (stainless steel 1.4404, stamped), clamp (stainless steel)

Delivery variants

- further diameters available on request
- gas and liquid tight as pre-fitted version

Size	Nominal width tube	Outer-Ø flange	Weight	Suitable for Hose I.D.	Order No.
(mm)	(inch)	(mm)	(kg/pcs)	(mm)	
•	RI-CLAMP DIN 32676; Stainle		= AISI 316L; (please select		
25	-	50,5	0,090	Ø 25	245-0025-2914
32	-	50,5	0,090	Ø 32	245-0032-2914
40	-	50,5	0,080	Ø 40	245-0040-2914
50	-	64,0	0,160	Ø 51	245-0050-2914
65	-	91,0	0,180	Ø 65	245-0065-2914
80	-	106,0	0,380	Ø 80	245-0080-2914
100	-	119,0	0,420	Ø 101	245-0100-2914
150	-	183	1,200	Ø 151	245-0150-2914
Adapter T	RI-CLAMP ISO 2852; Stainle	ss steel 1.4404 (stamped) =	: AISI 316L; (please select	the hose and the assembly	separately)
-	1"	50,5	0,09	Ø 25	245-0025-2923
-	1 1/2"	50,5	0,11	Ø 40	245-0040-2923
-	2"	64,0	0,16	Ø 51	245-0050-2923
-	2 1/2"	77,5	0,17	Ø 65	245-0065-2923
-	3"	91,0	0,35	Ø 76	245-0075-2923
-	4"	119,0	0,42	Ø 101	245-0100-2923
		Matching accessories; sea	I DIN 32676; Silicone, whit	е	
25	-	50,5	-	Ø 25	245-0025-8912
32	-	50,5	-	Ø 32	245-0032-8912
40	-	50,5	-	Ø 40	245-0040-8912
50	-	64,0	-	Ø 50	245-0050-8912
65	-	91,0	-	Ø 65	245-0065-8912
80	-	106,0	-	Ø 80	245-0080-8912
100	-	119,0	-	Ø 100	245-0100-8912

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/.

Matching accessories; Adapter for welding on DIN 32676

www.norres.com 1

CONNECT TRI-CLAMP FITTING 245





Size	Nominal width tube	Outer-Ø flange	Weight	Suitable for Hose I.D.	Order No.
(mm)	(inch)	(mm)	(kg/pcs)	(mm)	
25	-	50,5	-	Ø 25	245-0025-8913
32	-	50,5	-	Ø 32	245-0032-8913
40	-	50,5	-	Ø 40	245-0040-8913
50	-	64,0	-	Ø 50	245-0050-8913
65	-	91,0	-	Ø 65	245-0065-8913
80	-	106,0	-	Ø 80	245-0080-8913
100	-	119,0	-	Ø 100	245-0100-8913
		Matching accessories	; Clamp; stainless stell		
-	-	50,5	-	-	245-0025-8914
-	-	64,0	-	-	245-0050-8914
-	-	77,5	-	-	245-0055-8914
-	•	91,0	-	-	245-0065-8914
-	-	106,0	-	-	245-0080-8914
-	-	119,0	-	-	245-0100-8914
		Matching accessories; sea	al ISO 2852: Silicone, white		
-	1"	50,5	-	Ø 25	245-0025-8916
-	1 1/2"	50,5	-	Ø 40	245-0040-8916
-	2"	64,0	-	Ø 50	245-0050-8916
-	2 1/2"	77,5	-	Ø 65	245-0065-8916
-	3"	91,0	-	Ø 75	245-0075-8916
-	4"	119,0	-	Ø 100	245-0100-8916
	M	latching accessories; Adap	oter for welding on ISO 285	52	
-	1"	50,5	-	Ø 25	245-0025-8917
-	1 1/2"	50,5	-	Ø 40	245-0040-8917
-	2"	64,0	-	Ø 50	245-0050-8917
-	2 1/2"	77,5	-	Ø 65	245-0065-8917
-	3"	91,0	-	Ø 75	245-0075-8917
-	4"	119,0	-	Ø 100	245-0100-8917

Accessories



CONNECT SAFETY CLAMP ASSEMBLY 231



CONNECT MOULD ASSEMBLY 233



CONNECT PRESS ASSEMBLY 232

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.