



TRI-Clamp coupling to fit adapter acc. to DIN 32676

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant
- microbe and hydrolysis resistant

- good resistance to oil, gasoline, and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature range

- -40 °F to 195 °F

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- special colors: full colored

Size (in)	Outer-Ø flange (in)	Pipe I.D. (in)	Total Length (in)	Weight (lb/pcs)	Suitable for hose I.D. (in)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
1.260	1.988	1.260	2.362	0.132	32	245-0032-8500
1.496	1.988	1.496	2.559	0.154	38	245-0038-8500
1.969	2.520	1.969	2.638	0.265	50	245-0050-8500
2.559	3.583	2.598	2.638	0.397	65	245-0065-8500
3.150	4.173	3.189	2.835	0.441	80	245-0080-8500
3.937	4.685	3.937	3.031	0.728	100	245-0100-8500
4.921	6.102	4.921	3.583	1.058	125	245-0125-8500
5.906	7.205	5.906	4.016	1.477	150	245-0150-8500
7.874	9.193	7.874	4.429	2.117	200	245-0200-8500
Threaded; Suitable for Hose 356						
1.969	2.520	1.969	2.638	0.265	50	245-0050-8501
3.150	4.173	3.189	2.835	0.441	80	245-0080-8501
3.937	4.685	3.937	3.031	0.728	100	245-0100-8501
4.921	6.102	4.921	3.583	1.058	125	245-0125-8501
5.906	7.205	5.906	4.016	1.477	150	245-0150-8501
7.874	9.193	7.874	4.429	2.117	200	245-0200-8501
pre-fitted; (please select the hose separately)						
1.496	1.988	1.496	2.559	0.154	38	245-0038-8554
1.969	2.520	1.969	2.638	0.265	50	245-0050-8554
2.559	3.583	2.598	2.638	0.397	65	245-0065-8554
3.150	4.173	3.189	2.835	0.441	80	245-0080-8554
4.921	6.102	4.921	3.583	1.058	125	245-0125-8554
7.874	9.193	7.874	4.429	2.117	200	245-0200-8554