CONNECT 245 VAC-TRUCK





Tapered flange coupling system to fit adapter acc. to DIN 3016-3

Applications

- suction excavator
- municipal vehicle: sweeper, sweeping machine

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- When used vertically user must secure flange and hose with additional attachments
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

• -40°C to 90°C

Design

•

wall: special premium ether-polyurethane (Pre-PUR $^{\ensuremath{\texttt{B}}})$

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured
- gas and liquid tight as pre-fitted version

Size	Outer-Ø flange	Total Length	Weight	Suitable for Hose I.D.	item	Order No.
(mm)	(mm)	(mm)	(kg/pcs)	(mm)		
			rd version, 80 Shore I			
250	295	108	1,00	356-0250-0000	tapered flange, black, for screwing on	245-0250-8501
250	295	108	1,00	355-0254-5202	tapered flange, black, for screwing on	245-0250-8507
Soft version, 85 Shore A approx.						
250	295	108	1,00	356-0250-0000	tapered flange, black, for screwing on	245-0250-8505
pre-fitted, 85 Shore D approx.						
250	295	119	1,61	356-0250-0000	tapered flange, black, moulded	245-0250-8573
250	295	108	1,00	355-0254-5202; 356-0250-0000	reinforced tapered flange, black, moulded	245-0250-8754
Reinforced version, 85 Shore D approx.						
250	295	108	1,00	356-0250-0000	Reinforced tapered flange, black, for screwing on	245-0250-8701
Clamps						
250	-	-	1,50	-	Reinforced quick- release clamp	245-0250-8755
250	-	-	1,240	-	Quick-Release clamp	245-0250-8911

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/.